

# Updated Transport Assessment



<b>Ref</b>	JTP18_095
<b>Site Name</b>	Land South of Kelvedon Road, Tiptree
<b>Date</b>	November 2020

## Quality Assurance

Site name: Land South of Kelvedon Road, Tiptree

Client name: Marden Homes

Type of report: Updated Transport Assessment

Prepared by: Steve Amann BSc (Hons) MSc (Engr)

Signed

A handwritten signature in black ink, appearing to be "S. Amann".

Date: November 2020

Reviewed by: Fiona Hunter BSc(Hons)

Signed:

A handwritten signature in black ink, appearing to be "F. Hunter".

Date: November 2020



# Table of Contents

<b>1</b>	<b>INTRODUCTION.....</b>	<b>1</b>
	Background .....	1
	Brief.....	1
<b>2</b>	<b>POLICY CONTEXT.....</b>	<b>3</b>
	The National Planning Policy Framework (NPPF).....	3
	Essex Local Transport Plan 2011 .....	4
	Development Management Policies 2011 .....	4
	Colchester Local Plan.....	5
<b>3</b>	<b>EXISTING CONDITIONS .....</b>	<b>6</b>
	Site Location.....	6
	Highway Access to Development Area .....	6
	Public Transport Accessibility: Rail Services.....	6
	Public Transport Accessibility: Bus Services.....	6
	Walking and Cycling Assessment .....	7
	Walking.....	8
	Highway Safety Assessment .....	8
<b>4</b>	<b>DEVELOPMENT ACCESS .....</b>	<b>10</b>
	Highway Access .....	10
<b>5</b>	<b>TRAFFIC GENERATION .....</b>	<b>11</b>
	Proposed Development .....	11
	Residential Trip Rates .....	11
	Trip Distribution .....	12
<b>6</b>	<b>TRAFFIC IMPACT .....</b>	<b>13</b>
	Background Traffic Flows .....	13
	Assessment Year and Background Traffic Growth.....	13
	Committed Development .....	13
	Assessment of Traffic Impact.....	13
	Vehicle Parking.....	17
	Servicing.....	17
	Residential Travel Planning .....	17
<b>7</b>	<b>SUMMARY .....</b>	<b>19</b>
	Summary .....	19
	Conclusion.....	19

Land at Kelvedon Road, Tiptree  
**November 2020**



## **Appendices**

- Appendix 1 Site Location**
- Appendix 2 Public Transport Data**
- Appendix 3 Proposed Access Arrangement**
- Appendix 4 Illustrative Development Layout**
- Appendix 5 TRICS Data**
- Appendix 6 Census Information**
- Appendix 7 Traffic Data**
- Appendix 8 Network Flows**
- Appendix 9 Junctions 9 Output**
- Appendix 10 Stage One Safety Audit**

# 1 Introduction

## Background

- 1.1 Journey Transport Planning has been commissioned by Marden Homes to undertake a Transport Assessment in support of proposals for residential development on land to the south of Kelvedon Road Tiptree.
- 1.2 The proposal site is comprised of an area of land across 5.16 hectares occupied by a range of uses and is illustrated in **Appendix 1**.
- 1.3 This report provides a detailed assessment of the proposed location for the outlined development in respect to its suitability as a sustainable location in transport terms for the purpose of residential development and in terms of the adequacy of the local highway and transport network infrastructure to support such a proposal.
- 1.4 Specifically, this report provides a technical appraisal of how appropriate access can be achieved for a sustainable residential development on land to the south of Kelvedon Road Tiptree, Essex and sets out a detailed deliverable access strategy encompassing public transport, cycle, pedestrian and vehicular access. It demonstrates the level of access that will be required and provides an analysis of the likely trip distribution and assignment for the development generated traffic and the potential impact on the routes and junctions in terms of vehicular impact, public transport capacity and available cycle and pedestrian infrastructure.
- 1.5 This assessment is informed by the requirements of Colchester Borough Council and Essex County Council.
- 1.6 Fundamentally, the purpose of this assessment is to demonstrate that the development of 130 homes is deliverable in the context of both the existing transport infrastructure and moreover any impacts associated with additional traffic generated by the proposal can be accommodated on the transport network and will not have a deleterious impact on the operation of that network.

## Brief

- 1.7 The following matters have been considered in this appraisal:
  - Section 2 considers the way in which the proposals accord with and support the objectives of local, regional and national policy with respect to transport and movements.
  - Section 3 considers the existing site conditions and reviews the accessibility of the site by road, public transport, on foot and by bicycle, including an assessment of



highway safety, to illustrate that the site is easily accessible by a range of alternative transport modes.

- Section 4 outlines the development aspirations for the site and access proposals.
- Section 5 sets out the methodology for the calculation of traffic generation, trip distribution and assignment from the allocation site.
- Section 6 considers the potential traffic impact of an allocation utilising industry standard capacity assessment methodology and software as appropriate.
- Section 7 sets out a summary and conclusion to the Assessment.

## 2 Policy Context

- 2.1 The proposed development is subject to both national and local planning policy guidance with respect to transportation and its impact upon the local environment and surrounding infrastructure. A number of policies are directly pertinent to this site and are set out below.
- 2.2 Relevant policy guidance relating to new development, transport and land use planning is set out at the national and local level in the following documents:
- The National Planning Policy Framework;
  - The Essex 2011 Local Transport Plan;
  - Essex County Council's Development Management Policies 2011;
  - Colchester Borough Council Core Strategy (adopted 2008, amended 2014);
  - Colchester Borough Council Site Allocations DPD (adopted 2010); and
  - Colchester Borough Council Development Policies DPD (adopted 2010, amended 2014)
- 2.3 These documents set the context in which the site's proposals have been assessed.

### The National Planning Policy Framework (NPPF)

- 2.4 The National Planning Policy Framework sets out the Government's planning policies for England and how these should be applied. The NPPF is a material consideration in planning decisions.
- 2.5 The purpose of the planning system is to contribute to the achievement of sustainable development. At a very high level, the objective of sustainable development can be summarised as meeting the needs of the present without compromising the ability of future generations to meet their own needs.

### Promoting Sustainable Transport

- 2.6 The NPPF in promoting sustainable transport considers in paragraph 108 that for sites to be allocated for development in plans, or specific applications for development, it should be ensured that:
- (a) *appropriate opportunities to promote sustainable transport modes can be – or have been – taken up, given the type of development and its location;*
  - (b) *safe and suitable access to the site can be achieved for all users; and*
  - (c) *any significant impacts from the development on the transport network (in terms of capacity and congestion), or on highway safety, can be cost effectively mitigated to an acceptable degree.*
- 2.7 The NPPF goes on to re-iterate in paragraph 109 that **Development should only be prevented or refused on highways grounds if there would be an unacceptable impact on highway safety, or the residual cumulative impacts on the road network would be severe.**

- 2.8 The NPPF sets out in the context of applications for development in paragraph 110 that they should:
- (a) give priority first to pedestrian and cycle movements, both within the scheme and with neighbouring areas; and second – so far as possible – to facilitating access to high quality public transport, with layouts that maximise the catchment area for bus or other public transport services, and appropriate facilities that encourage public transport use;*
  - (b) address the needs of people with disabilities and reduced mobility in relation to all modes of transport;*
  - (c) create places that are safe, secure and attractive – which minimise the scope for conflicts between pedestrians, cyclists and vehicles, avoid unnecessary street clutter, and respond to local character and design standards;*
  - (d) allow for the efficient delivery of goods, and access by service and emergency vehicles; and*
  - (e) be designed to enable charging of plug-in and other ultra-low emission vehicles in safe, accessible and convenient locations.*
- 2.9 The chapter concludes in paragraph 111 that ... *All developments that will generate significant amounts of movement should be required to provide a travel plan, and the application should be supported by a transport statement or transport assessment so that the likely impacts of the proposal can be assessed.*

### Essex Local Transport Plan 2011

- 2.10 The 2011 Essex Local Transport Plan sets out the County Council's aims and objectives for transport and infrastructure for the next ten-year period and provides the policy framework to achieve the objectives.
- 2.11 Policy 2 Integrated Development sets out the County's position in relation to integrated planning and states that:
- Transport and land-use planning will be used together to secure new development at the most appropriate and sustainable locations by: working closely with district planning authorities to enable a better balance of new homes, jobs and services; locating new developments in areas which are accessible to key services by sustainable forms of transport; ensuring new developments provide for sustainable transport and effective travel planning; requiring new developments to provide appropriate transport infrastructure in line with the Council's current development management policies; and making the most effective use of all available funding sources by co-ordinating the delivery of ECC and development funded works.*

### Development Management Policies 2011

- 2.12 The aims and objectives of LTP policy are supported by the policies set out in the Development Management Policies 2011 which provides specific requirements in terms of transport access and new development in relation to the County Council's functional route hierarchy.

- 2.13 The site is bordered by Kelvedon Road to the north which is classified as a Secondary Distributor Road in the hierarchy.
- 2.14 The proposals take full regard of and accord with the policies set out as they apply to the road and access options for the site.

### Colchester Local Plan

- 2.15 The Colchester Borough Local Plan is contained with the following documents:
  - Colchester Borough Council Core Strategy (adopted 2008, amended 2014)
  - Colchester Borough Council Site Allocations DPD (adopted 2010)
  - Colchester Borough Council Development Policies DPD (adopted 2010, amended 2014)
- 2.16 Whilst these documents represent the currently adopted Local Plan for development in the Borough; this plan is currently being replaced to ensure its compliance with National Planning Policy.
- 2.17 The Colchester Borough Council CBC Local Plan 2017-2033 Publication Draft, remains as the 'emerging' Local plan for Colchester.
- 2.18 In consideration of the above, the following Local Plan policies have relevance to the site and the proposals.
- 2.19 Policy SG5: – Centre Hierarchy identifies Tiptree as a District Centre with a good range of supporting facilities and amenities.
- 2.20 Policy SS14: identifies the proposal site as being suitable to support residential development, open space and community infrastructure.
- 2.21 Policy DM21: Sustainable Access to Development, sets out the requirement for developments to consider all forms of access placing emphasis on sustainable means and also sets out that: *“Development will only be allowed where there is physical and environmental capacity to accommodate the type and amount of traffic generated in a safe manner. Developments that generate significant amounts of movement will require a Transport Statement or Transport Assessment in line with the thresholds set in the latest Essex County Council development management policies relating to highways.”*
- 2.22 Policy DM 21 also sets out that significant residential developments will be required to provide residential travel packs in accordance with Essex County Council guidance.
- 2.23 Policy DM22: Parking sets out that the amount of car parking to be provided in association with new residential development will be assessed using the most recent local Parking Guidance.
- 2.24 This appraisal and the proposals for the site fully take into consideration the policies set out in the adopted and emerging Local Plan for Colchester.



## 3 Existing Conditions

### Site Location

- 3.1 The proposal site is located in Tiptree, directly to the south of Kelvedon Road B1023 which runs north west to south east past the site. The location of the site in relation to the local area is shown in **Appendix 1**.

### Highway Access to Development Area

- 3.2 The routes in the vicinity of the area of land being considered for development and links to the local area road network have been examined in detail.
- 3.3 Kelvedon Road runs north west to south east to the north of the site and links Tiptree centre to the east with Kelvedon and the A12 to the west.
- 3.4 Kelvedon Road is a single carriageway road with an effective running width of 6.0 metres. It is subject to the 30mph speed limit as it passes to the north of the site. The road has the benefit of street lighting and continuous footway provision to both sides as it passes the site.

### Public Transport Accessibility: Rail Services

- 3.5 Kelvedon operates the closest mainline rail station to the development site and is around 3 miles from the site.
- 3.6 Currently, there is a very frequent service during peak periods from Kelvedon to either Colchester or London Liverpool Street. During the rest of the day the service operates on a reasonably frequent basis with trains to London every 15 minutes or so.
- 3.7 There is a dedicated car park (around 280 Spaces) at the station. The station also has the benefit of sheltered cycle stands for cycle parking.

### Public Transport Accessibility: Bus Services

- 3.8 The provision of bus based public transport in the area has been assessed in terms of access to routes, frequencies of services and levels of reliability. The quality of the bus infrastructure in the area has also been assessed in respect of the provision and quality of shelters, information and seating.
- 3.9 Bus accessibility is measured by reference to the number and frequency of services available within easy walking distance of the proposal site. Easy walking distance is considered to be up to 400 metres in the case of accessing bus based public transport. This equates to a five minute walk time assuming a walk speed of 80 metres per minute.
- 3.10 The whole of the site is within 400m of bus stops on Kelvedon Road near to Oak Road and East Road. From these stops, numbers 91 provides a service between Tollesbury and Witham on a two hourly basis. In addition, stops on Maldon Road B1022 to the east within 500m of

the site provide access to the 75 service which operates between Maldon and Colchester on a half hourly basis.

3.11 **Table 3.1** summarises the bus services available from the stops in the vicinity of the site.

**Table 3.1 Bus Service Summary**

Bus Number	Route	Frequency
91	Witham to Tollesbury	Mon-Sat 2 hourly freq
75	Maldon- Colchester	Mon-Sat Hal hourly Sunday 2 hourly

3.12 With a regular bus services available between Maldon and Colchester with potential connections to destinations further afield, the proposal site is well provided for by public transport.

3.13 The routes and timetables are held in **Appendix 2**.

### Walking and Cycling Assessment

3.14 This Assessment has considered the accessibility and integration of the site to local amenities and facilities on foot and by bicycle.

### Cycling

3.15 Cycling has the potential to substitute for short car trips, especially those less than 5km. Cycle access to the site has been considered in detail and for the purposes of cycle accessibility, a cycle time of 20 minutes, which equates to 5km at an average speed of 15kph, has been assumed.

3.16 The 5km catchment area within an acceptable cycling distance of the site includes Tiptree and Kelvedon covers the full range of local facilities and amenities including:

- Supermarket;
- Hotel;
- Employment Areas;
- Churches;
- Nursery Primary and Secondary Educational facilities;
- Pubs and Restaurants;
- Banks and Financial Services;
- Post Offices;
- Country Park;
- Doctors / Dental Surgeries;
- Chemists;
- Village Halls; and
- Mainline rail station

- 3.17 The site is therefore within reasonable cycling distance of a good range of local amenities and employment opportunities and as such, is considered to have very good levels of accessibility and integration opportunities in line with the aims and objectives of the National Planning Policy Framework.
- 3.18 There is no specific cycle infrastructure in the vicinity of the site.

### Walking

- 3.19 With respect to pedestrian access, a walk time of ten minutes is generally considered the maximum acceptable to directly access any local facility or amenity and equates to a distance of 800 metres at an average speed of 5kph.
- 3.20 Whilst there are limited facilities and amenities within the 800 metre pedestrian catchment area from the centre of the site, The National Planning Policy Framework identifies walking as the most important mode of travel at the local level which offers the greatest opportunity to replace short car trips of less than 2km. The site is within acceptable walking distance of:
- Primary Schools
  - Local Shops
  - Post Office
  - Chemist
  - General Store
  - Doctors
- 3.21 The provision of pedestrian routes through the proposal site will also enable further direct pedestrian connection between the site and the surrounding built up area, thus integrating the development into the existing community.
- 3.22 The site is therefore considered to be within reasonable walking distance of a good range of local amenities and as such, is considered to have very good levels of accessibility and integration opportunities in line with policy requirements.

### Highway Safety Assessment

- 3.23 A highway safety assessment has been undertaken for the highway network surrounding the site, based upon Essex County Council Personal Injury Accident (PIA) data obtained for the three-year period October 2017 to October 2020.
- 3.24 A total of two personal injury accidents were recorded over the three-year period both of which were classed as serious.
- 3.25 The recorded accidents were recorded to the west of the site on Kelvedon Road one at the junction of Kelvedon Road and Vine road and the other further west on Kelvedon Road near the junction with Primrose Lane.
- 3.26 The accident data reviewed above identifies the absence of any specific accident pattern with no identified clusters in the vicinity of the site.

Land at Kelvedon Road, Tiptree  
**November 2020**



- 3.27 It is considered that in view of the foregoing review there are no prevailing highway safety concerns in relation to site and the surrounding area, and moreover residential development on the site and the resulting increase in traffic would not have a significantly detrimental impact on that safety record.

## 4 Development Access

### Highway Access

- 4.1 Access to the site has been considered in the context of the aims and objectives of policies set out in the Essex Development Management Policies 2011 which provides specific policy requirements in terms of transport access and new development in relation to the County Council's functional route hierarchy.
- 4.2 The site is bordered by Kelvedon Road to the north which is classified as a Secondary Distributor in the hierarchy.
- 4.3 The proposals take full regard of and accord with the policies set out as they apply to the road and access options for the site.
- 4.4 The access requirements for the site have been also considered in the context of the guidance set out in the latest iteration of the Essex Design Guide 2018. in accordance with the guidance a Type E Minor Access Road would provide a suitable and appropriate level of access to the site to accommodate the development aspirations for the site.
- 4.5 An Access road with a 5.5m carriageway and two 2.0m footways in accordance with the Type E specification will be provided through the site to accommodate the needs of cyclists, pedestrians and other vehicles and will be designed to achieve a 20mph environment.
- 4.6 The layout of the development will accord with the Road Type criteria set out in the residential road layout guidance as produced by Essex County Council.
- 4.7 Access would be taken directly from Kelvedon Road to the north of the site. The access form has been considered in the context of the level of development proposed and the existing traffic levels and also the advice provided in CD 123. In the context of that advice, the potential to provide a mini-roundabout to the site has been assessed as it would have the potential to provide sufficient capacity to accommodate through route traffic for the Grange Road site to the south in the future.
- 4.8 A mini roundabout access arrangement can be provided within land within the site and the control of the highway authority.
- 4.9 The roundabout has been the subject of a Stage One Safety Audit which identifies that there are no significant highway safety issues with its design and as such is designed in accordance with current requirements. The safety audit is held in **Appendix 10**.
- 4.10 The proposed mini-roundabout access arrangement is held in **Appendix 3** and would be suitable to accommodate both the site development traffic and an additional element associated with the Grange Road site and would also accommodate the private access to the land to the north of Kelvedon Road.
- 4.11 Two units are proposed to take access directly via Kelvedon Road via a single private drive arrangement, consistent with the arrangements for existing houses on Kelvedon Road.

## 5 Traffic Generation

### Proposed Development

- 5.1 The proposals for the site comprise a sustainable development of 130 dwellings with associated infrastructure, open space, parking and access.
- 5.2 An illustrative development layout is held in **Appendix 4**.
- 5.3 In order to forecast the likely travel demand associated with the proposed development allocation for the site, a detailed interrogation of the TRICS Version 7 trip generation database has been undertaken.
- 5.4 The TRICS database contains a wide range of information relating to travel patterns and behaviours associated with various development types and locations and it provides a robust and accepted basis for assessing the likely impact in terms of travel demand associated with new development.
- 5.5 For the purposes of this appraisal, information from the TRICS database has been disaggregated by development type, mode and location in order to provide a development trip generation profile that corresponds closely with the characteristics of the proposal site.
- 5.6 The information supplied from the database provides an estimate of the likely number of vehicular trips to and from the development area. This information in turn informs the infrastructure requirements of the development in terms of highway capacity, public transport capacity, cycle movements and pedestrian movements.

### Residential Trip Rates

- 5.7 Appropriate vehicular residential trip rates have been obtained from the TRICS database and full details of the TRICS Version 7 residential trip rate data are held in **Appendix 5**.
- 5.8 The trip rates for private housing have been extracted from the database for the AM (08:00-09:00) and PM (17:00-18:00) peak hours and the forecast unrestrained vehicular trip rate generation associated with the proposed residential site is summarised in **Table 5.1**. The TRICS data assumes a standalone residential development without the benefit of travel planning or improvements to public transport and sustainable modes of travel.

**Table 5.1 Residential Trip Rates**

Land Use	AM 08:00-09:00		PM 17:00-18:00	
	Arrival Rates	Departure Rates	Arrival Rates	Departure Rates
Private Housing	0.140	0.384	0.338	0.156

- 5.9 The residential trip rate data has been applied to the ultimate development capacity of the site to provide a robust estimate of the likely vehicular trips that could be associated with a residential development on the site. For the purposes of this assessment the impact of a development of up to 130 units has been assessed. **Table 5.2** summarises the vehicular trip generation based on the likely tenure and type of residential units envisaged.

**Table 5.2 Vehicular Trip Generation 130 Dwellings**

Land Use	AM 08:00-09:00		PM17:00-18:00	
	Arrivals	Departures	Arrivals	Departures
130 Dwellings	18	50	44	20

- 5.10 **Table 5.2** indicates that a development of 130 residential units as proposed could generate up to 68 vehicular trips in the AM peak and 64 vehicular trips in the PM peak.

### Trip Distribution

- 5.11 The forecast development traffic has been assigned on the network in accordance with local highway network in accordance with the Census Travel to Work Origin and Destination data for the resident population of Tiptree who drive to work. The Census data is held in **Appendix 6**.
- 5.12 The Google Maps satellite navigation route finder application was used to verify the distribution of vehicle trips on the local highway network.
- 5.13 Table 5.3 provides a summary of the Development Traffic Trip Distribution and is applied to the network traffic flow diagrams in **Appendix 8**.

**Table 5.3 Vehicular Trip Distribution**

Link	AM 08:00-09:00		PM17:00-18:00	
	Arrivals	Departures	Arrivals	Departures
<b>Kelvedon Road North/West</b>	62%	62%	62%	62%
London Road East	62%	62%	62%	62%
<b>Kelvedon Road South/East</b>	38%	38%	38%	38%
B1022 South	38%	38%	38%	38%

## 6 Traffic Impact

### Background Traffic Flows

- 6.1 Existing traffic data has been obtained via manually classified junction turning count (MCC) undertaken by Advanced Transport Research (ATR) on Tuesday 24<sup>th</sup> January 2019 at the following junctions:
- Maypole Road/Colchester Road/Oak Road Priority Junction
  - Kelvedon Road/Maypole Road/Church Road/Maldon Road Mini Roundabout
  - Vine Road/Townsend Road/Kelvedon Road Crossroads
  - Kelvedon Road/Oak Road
- 6.2 The full set of observed traffic data, comprising manually classified turning counts is contained in **Appendix 7**.
- 6.3 It was identified that on the day of the survey Vine Road was closed by road works which would have resulted in traffic diverting via Maldon Road/Maypole Road. In view of this the traffic surveyed for the Colchester United FC/Grange Road was added to the ins and outs for Vine Road. This will inevitably result in an element of double counting across the network and at the junction and as such provides a robust basis for the assessment.
- 6.4 For the purposes of this assessment the observed AM and PM network peak hour periods of 08:00 to 09:00 and 17:00 to 18:00 have been used, as determined from the surveys undertaken on site. The observed peak hour network traffic flows are illustrated by the network diagrams contained in **Appendix 8**.

### Assessment Year and Background Traffic Growth

- 6.5 An assessment of the impact of the proposed development upon the local highway network in the vicinity of the site comprising the study area has been undertaken. An assessment year of 2025, reflecting the planning timescale, has been applied to the assessment of the local highway network adjacent to the site. The use NTEM Temprow traffic growth factors used incorporate an element of growth to represent consented development schemes and as such provide a robust forecast for the assessment.

### Committed Development

- 6.6 The traffic associated with the ongoing development site at Grange Road has been included in this assessment with the flow information taken directly from the associated Transport Assessment undertaken by Ardent Consulting Engineers in support of the development. The committed development traffic is shown in the network flow diagrams in **Appendix 8**.

### Assessment of Traffic Impact

- 6.7 The traffic impact of the proposals has been examined in terms of the total additional external vehicle trips forecast from the development based on the distribution methodology set out in Section 5 above.



- 6.8 Principally, this section considers the immediate highway network, the number of additional trips in the AM and PM peak periods (the critical periods for network assessment), the ability of the existing network to accommodate additional traffic, the potential mitigation that may be required and an assessment of the deliverability of that mitigation.
- 6.9 Detailed assessments of the capacity of the following junctions has been undertaken for AM and PM peak periods with and without development scenarios utilising the Junctions 9 ARCADY/PICADY software.
- Maypole Road/Colchester Road/Oak Road Priority Junction
  - Kelvedon Road/Maypole Road/Church Road/Maldon Road Mini Roundabout
  - Vine Road/Townsend Road/Kelvedon Road Crossroads
  - Kelvedon Road/Oak Road Priority Junction
  - Kelvedon Road Site Access Roundabout
- 6.10 The Junctions 9 capacity assessments set out the maximum Ratio of Flow to Capacity (RFC) and Maximum Queue (vehicles) for each arm of the junction. Generally, where the RFC of an arm is greater than 1.0 then the arm is said to be operating at over its theoretical capacity and would be expected to suffer levels of queuing and delay. An arm with an RFC of between 0.85 and 1.0 is considered to be approaching its practical capacity and some queuing and delay may be expected to occur.

#### Maypole Road/Colchester Road/Oak Road Priority Junction

- 6.11 A detailed assessment of the impact of the potential development upon the priority junction has been undertaken and is considered in **Table 6.1** below.

**Table 6.1 Maypole Road/Colchester Road/Oak Road PICADY Junction Summary**

		Maypole Road		Oak Road	
		RFC	Q	RFC	Q
AM	2025 Total Flows	0.20	0.3	0.20	0.3
PM	2025 Total Flows	0.04	0.0	0.32	0.5

- 6.12 The full Junctions 9 PICADY outputs for the junction are contained in **Appendix 9**.
- 6.13 The PICADY analysis indicates that in the 2025 forecast year with the development, the junction will operate within capacity during all time periods.

#### Kelvedon Road/Maypole Road/Church Road/Maldon Road Mini Roundabout

- 6.14 A detailed assessment of the operation of the Kelvedon Road/Maypole Road/Church Road/Maldon Road double Mini Roundabout junction has been undertaken and is considered in **Table 6.2** below.
- 6.15 The roundabout was modelled as 2 separate 3 arm mini roundabouts in accordance with current guidance and are referred to as the north and south roundabouts respectively.

**Table 6.2 North Roundabout Mini Roundabout**

		Roundabout Link		Kelvedon Road		Maypole Road	
		RFC	Q	RFC	Q	RFC	Q
AM	2025 Base	0.53	1.2	0.35	0.6	0.90	7.9
PM	2025 Base	0.81	4.3	0.67	2.2	0.57	1.4
AM	2025 Total Flows	0.54	1.3	0.38	0.7	0.92	9.4
PM	2025 Total Flows	0.84	5.4	0.69	2.3	0.58	1.5

**Table 6.3 South Roundabout Mini Roundabout**

		Roundabout Link		Church Road		Maldon Road	
		RFC	Q	RFC	Q	RFC	Q
AM	2025 Base	0.61	1.7	0.64	1.9	0.78	3.6
PM	2025 Base	0.84	5.3	0.52	1.2	0.79	3.9
AM	2025 Total Flows	0.63	1.9	0.65	2.0	0.79	3.9
PM	2025 Total Flows	0.84	5.5	0.52	1.2	0.81	4.4

- 6.16 The Junctions 9 North Roundabout PICADY assessment illustrated in **Table 6.2** identifies that the junction will operate in excess of capacity with an RFC of 0.9 and queuing up to 8 vehicles identified on Maypole Road in the AM peak in the 2025 base case without the development, this is identified to increase by just 0.2 with the development with an increase in queuing of 1 vehicle. It is considered that this increase will not be perceptible when considered against the daily fluctuations at the junction and as such is not considered to be material of significant in the context of highway capacity and traffic impact.
- 6.17 The Junctions 9 South Roundabout PICADY assessment illustrated in **Table 6.3** identifies that the junction will operate within capacity in the design year with and without the development.
- 6.18 The full Junctions 9 PICADY outputs for the junction are contained in **Appendix 9**.

#### Vine Road/Townsend Road/Kelvedon Road Crossroads

- 6.19 A detailed assessment of the operation of the Vine Road/Townsend Road/Kelvedon Road junction has been undertaken and is considered in **Table 6.4** below.

**Table 6.4 Vine Road/Townsend Road/Kelvedon Road Crossroads PICADY Summary**

		Kelvedon Road		Vine Road		Kelvedon Road West		Townsend Road	
		RFC	Q	RFC	Q	RFC	Q	RFC	Q
AM	2025 Total Flows	0.11	0.2	0.28	0.4	0.11	0.1	0.18	0.2
PM	2025 Total Flows	0.16	0.2	0.30	0.5	0.09	0.1	0.07	0.1

6.20 The Junctions 9 PICADY assessment illustrated in **Table 6.4** identifies that the junction will operate comfortably within the operational capacity of the junction for the design year 2025 with the site development flows in both the AM and PM peak with no significant queuing or delay predicted.

6.21 The full Junctions 9 PICADY outputs for the junction are contained in **Appendix 9**.

#### Kelvedon Road/Oak Road Junction Assessment

6.22 A detailed assessment of the impact of the potential development upon the priority junction has been undertaken and is considered in **Table 6.5** below.

**Table 6.5 Maypole Road/Colchester Road/Oak Road PICADY Junction Summary**

		Kelvedon Road		Oak Road	
		RFC	Q	RFC	Q
AM	2025 Total Flows	0.01	0.0	0.37	0.6
PM	2025 Total Flows	0.01	0.0	0.09	0.1

6.1 The PICADY analysis indicates that in the 2025 forecast year with the development, the junction will operate within capacity during all time periods.

6.2 The full Junctions 9 PICADY outputs for the junction are contained in **Appendix 9**.

#### Site Access Roundabout Junction Assessment

6.3 A detailed assessment of the operation of the Site Access Mini Roundabout has been undertaken and is considered in **Table 6.6** below.

**Table 6.6 Site Access Arcady Summary**

		Kelvedon Rd E		Site Access		Kelvedon Rd W	
		RFC	Q	RFC	Q	RFC	Q
AM	2025 Total Flows	0.69	2.4	0.13	0.2	0.36	0.6
PM	2025 Total Flows	0.33	0.5	0.04	0.0	0.83	5.2

6.4 The Junctions 9 Arcady assessment illustrated in **Table 6.6** identifies that the junction will operate within the operational capacity of the junction for the design year 2025 with the site development flows in both the AM and PM peak with no significant queuing or delay predicted.

- 6.5 The full Junctions 9 ARCADY outputs for the junction are contained in **Appendix 9**.
- 6.6 In summary, the detailed network capacity analysis identifies that additional vehicular trips that the proposed development would generate would not have a significant or material impact in terms of either highway capacity or safety and moreover can be accommodated within the capacity of the existing network.

### Vehicle Parking

- 6.7 Car parking for the proposal is proposed in accordance with the minimum standards set out in the Essex Planning Officers Association Standards for Parking as appropriate for residential developments. Cycle parking is also be provided in accordance with current standards.
- 6.8 Car parking is provided in accordance with the following schedule:
- |                                 |                 |            |
|---------------------------------|-----------------|------------|
| • 1 space per 1 bed units       | 9 one bed units | 9 spaces   |
| • 2 spaces per 2 bed plus units | 121 units       | 242 spaces |
| • 0.25 visitor spaces per house | 130 units       | 33 spaces  |
| • Total                         |                 | 284 Spaces |

### Servicing

- 6.9 The proposed access and internal layout will be designed in accordance with current Essex County Council standards to accommodate the delivery and servicing requirements of a range of vehicles including emergency vehicles and refuse vehicles.

### Residential Travel Planning

- 6.10 The provision of travel plans, travel plan groups and travel plan co-ordination services will be fundamental to ensuring that the development promotes sustainable alternatives to sole occupancy car use not only in its implementation but throughout the life of the proposals.
- 6.11 This approach will help the development manage its own travel demand at source rather than relying on outside agencies to deal with the travel consequences of the development. Additionally, travel planning will also seek to reduce, over time, through the setting of targets for modal shift, the numbers of vehicle movements associated with the proposals. This will mean that in time there will be reductions in the number of sole occupancy trips associated with the development on the network as the development becomes established.
- 6.12 Taking the baseline trip generation as a starting point at the occupation of various phases of the development, achievable targets for traffic reduction will be set and monitored throughout the early stages of the development. A variety of schemes and measures to reduce sole occupancy trips will be put into action and the effectiveness of these schemes will be monitored against the set targets. The following list provides examples of the various travel plan measures applicable to residential uses which can be promoted for this development:
- Site pedestrian and cycle permeability;
  - Sustainable modal hierarchy;



- Car sharing database;
- Taxi buddy schemes;
- Residents Travel Plan Packs giving information on the alternatives available;
- Discounted public transport travel vouchers;
- Promotion of cycle routes to the development;
- Regular promotion including e-mail, posters and flyers to maintain or increase the level of participation;
- Improvements to the cycle infrastructure; and
- Providing for home-working (Broadband access/home office rooms etc.)

6.13 The travel plan measures set out above have the ability to effect a reduction in vehicular movements associated with the proposals and will over time ensure the sustainability of the development. The measures will be promoted as a part of any proposals coming forward and are an integral part of the planning process and as such, will be deliverable as a part of those proposals. In consideration of the target modal shift potential, discounts on trip rates for the development will be appropriate.

6.14 As a part of the proposals, a Residential Travel Information Pack will be provided for each new dwelling.

## 7 Summary

### Summary


- 7.1 This report provides an assessment of the likely transport impacts arising from the erection of up to 130 dwellings and with associated parking, public open space, landscaping, sustainable drainage system (SUDs) and vehicular access points from Kelvedon Road.
- 7.2 The assessment considers impact of the proposed development and its corresponding trip generation on the transport infrastructure.
- 7.3 The assessment demonstrates that the site is a suitable location for sustainable development and has the benefit of being accessible to a full range of key services and amenities to support the development and also is in accordance with the sustainability framework.
- 7.4 Residential Travel Packs are proposed as a part of the proposals and will assist in managing the traffic impact of the development.
- 7.5 A comprehensive trip generation analysis has been undertaken in order to understand the impacts, in terms of transport and traffic that the proposals will engender.
- 7.6 The assessment identifies that the proposals will not have a significant or material impact on the operation of the local highway network.
- 7.7 The capacity assessment demonstrates that the proposal site can be delivered without having a detrimental impact on the local transport infrastructure in the vicinity of the site and can be accommodated for the purposes of capacity and safety.

### Conclusion


- 7.8 The assessment clearly demonstrates that the proposed development of 130 dwellings on land to the south of Kelvedon Road, Tiptree will not have a material or significant impact on the operation of the local road network.
- 7.9 The assessment also demonstrates that the proposed development is suitably located to access key services, facilities and amenities by means other than private vehicles.
- 7.10 In consideration of the above, there are no substantive transport or access reasons why the proposals as submitted should not receive planning permission.



**Appendix 1**  
**Site Location**



KELVEDON ROAD



Tower House

Water Tower

Golden Warren

Coronation Cottages

Tower End

Ponys Farm

100

56

El Sub Sta

501

67.9m

El Sub Sta

Pond

The Gables

Pond

Track

Stourton

Baynards Primary School

Colt Farm

B 1023

The Paddock

Revelors Farm

Gwy

Patrick Stroud Designs Ltd,  
10 Hurstwood Avenue,  
Brentwood,  
Essex  
CM15 9HT  
T: 01277 260130 M 07955 687623  
E: patrickjstroud@btinternet.com

Client :  
**MARDEN.HOMES**  
Project :  
**LAND.AT.KELVEDON.ROAD,**  
**TIPTREE**  
Drawing :  
**LOCATION.PLAN**

Scale : **1:1250@A3**  
0 25 50  
Status :  
**PLANNING**  
Dwg No : **2017-116-01**  
Rev :  
■

© THIS DRAWING IS THE COPYRIGHT OF GO PLANNING LTD.  
It shall not be in any way used or reproduced without their prior written consent. All dimensions are to be checked on site or in the workshop prior to commencing any work. Work only to figured dimensions. Any discrepancies are to be reported to the Architect.





**Appendix 2**  
**Public Transport Data**

## Hedingham 91 Witham-Tollesbury

### Mondays to Fridays (from 27 August 2017)

	service no.	91	91	91	91	91	91	91	91	91	91	91
	notes											
Witham, Morrisons	-	-	-	0840	0955	1125	1345	1603	1633	1755	-	
Witham, Rail Station Stop 2	-	0700	0753	0842	0958	1128	1348	1606	1635	1758	1905	
Witham, The George	-	0702	0755	0845	1000	1130	1350	1608	1638	1800	1908	
Kelvedon, The Railway Tavern	0646	0711	0804	0852	1009	1139	1359	1617	1645	1809	1916	
Feering, Gore Pit Corner	0647	0714	0807	0854	1012	1142	1402	1620	1647	1812	1917	
Inworth, The Prince of Wales	0650	0717	0810	0857	1015	1145	1405	1623	1650	1815	1920	
Tiptree, Windmill Green	0653	0720	0814	0859	1018	1148	1408	1626	1651	1818	1923	
Tiptree, The Centre	0654	0722		0900	1020	1150	1410	1628s		1820	1924	
Tolleshunt Knights, Top Road	0659	0729		0904	1027	1157	1417	1635		1827	1929	
Tolleshunt D'Arcy, The Red Lion	0703	0733		0908	1031	1201	1421	1639		1831	1933	
Tollesbury, The Square	0708	0738		0913	1036	1206	1426	1644		1836	1938	
Tiptree, The New Times	-	-	0817	-	-	-	-	-	1654	-	-	
Tiptree, The Centre	-	-	0820	-	-	-	-	-	1656	-	-	

## Hedingham 91 Witham-Tollesbury

### Saturdays (from 27 August 2017)

	service no.	91	91	91	91	91
	notes					
Witham, Morrisons	-	0820	0950	1200	1430	1733
Witham, Rail Station Stop 2	-	0822	0952	1202	1432	1735
Witham, The George	-	0825	0955	1205	1435	1738
Kelvedon, The Railway Tavern	0712	0832	1002	1212	1442	1745
Feering, Gore Pit Corner	0714	0834	1004	1214	1444	1747
Inworth, The Prince of Wales	0717	0837	1007	1217	1447	1750
Tiptree, Windmill Green	0719	0839	1009	1219	1449	1752
Tiptree, The Centre	0720	0840	1010	1220	1450	1753
Tolleshunt Knights, Top Road	0724	0844	1014	1224	1454	1757
Tolleshunt D'Arcy, The Red Lion	0728	0848	1018	1228	1458	1801
Tollesbury, The Square	0733	0853	1023	1233	1503	1806

## Hedingham 91 Tollesbury-Witham

### Mondays to Fridays (from 27 August 2017)

	service no.	91	91	91	91	91	91	91	91	91
	notes									
Tollesbury, The Square	-	0710	-	0910	1040	1300	1518	1710	1825	1940
Tolleshunt D'Arcy, The Red Lion	-	0715	-	0915	1045	1305	1523	1715	1828	1943
Tolleshunt Knights, Top Road	-	0719	-	0919	1049	1309	1527	1719	1830	1945
Tiptree, The Centre	0634	0726	0821	0926	1056	1316	1534	1726	1835	1950
Tiptree, Windmill Green	0635	0727	0823	0927	1057	1317	1535	1727	1837	1952
Inworth, The Prince of Wales	0640	0732	0824	0932	1102	1322	1540	1732	1839	1954
Feering, Gore Pit Corner	0643	0735	0826	0935	1105	1325	1543	1735	1841	1956
Kelvedon, The Railway Tavern	0646	0738	0827	0938	1108	1328	1546	1738	1843	1958
Witham, The George	0655	0747	0835	0947	1117	1337	1555	1747	1851	-
Witham, Rail Station	0658	0750	0837	0950	1120	1340	1558	1750	1853	-
Witham, Morrisons	-	-	0838	0953	1123	1343	1601	1753	-	-

## Hedingham 91 Tollesbury-Witham

**Saturdays** (from 27 August 2017)




service no. 91 91 91 91 91 91 91

notes

<b>Tollesbury</b> , The Square	0737	0907	1107	1337	1552	-	1810
<b>Tolleshunt D'Arcy</b> , The Red Lion	0740	0910	1110	1340	1555	-	1813
<b>Tolleshunt Knights</b> , Top Road	0742	0912	1112	1342	1557	-	1815
<b>Tiptree</b> , The Centre	0747	0917	1117	1347	1602	1701	1822
<b>Tiptree</b> , Windmill Green	0749	0919	1119	1349	1604	1703	1824
<b>Inworth</b> , The Prince of Wales	0751	0921	1121	1351	1606	1705	1826
<b>Feering</b> , Gore Pit Corner	0753	0923	1123	1353	1608	1707	1828
<b>Kelvedon</b> , The Railway Tavern	0755	0925	1125	1355	1610	1709	-
<b>Witham</b> , The George	0803	0933	1133	1403	1618	1717	-
<b>Witham</b> , Rail Station	0805	0935	1135	1405	1620	1719	-
<b>Witham</b> , Morrisons	0806	0936	1136	1406	1621	1720	-




**Appendix 3**  
**Proposed Access Arrangement**




client: Marden Homes	title: Proposed Mini-Roundabout Access	date: 01/10/2018	scale @ A3 1:500
project: Kelvedon Road Tiptree	status: Planning (not for construction)	drawn:	Revision
discipline: Transport Planning	project no: JTP 07718	chk'd: SAA	dwg no: DR2





59.4m



FTA Design Articulated Vehicle (1990)  
Overall Length 16.480m  
Overall Body Height 3.570m  
Min Body Ground Clearance 0.270m  
Max Track Width 3.470m  
Lock-to-lock time 3.65s  
Curb to Curb Turning Radius 6.550m

Water tower

Golden Warren

Coronation Cottages

Tower End

Ponys Farm

The

client: Marden Homes

project: Kelvedon Road Tiptree

discipline: Transport Planning

title: Articulated HGV Swept Path 3 of 3

status: Planning (not for construction)

project no. JTP 07718

date: 01/10/2018

drawn

chk'd

SAA

scale @ A3  
1:500

Revision


dwg no.

DR4



Journey  
transport planning



59.4m





FIA Design Articulated Vehicle (1998)  
 Overall Length 12.450m  
 Overall Width 2.570m  
 Overall Body Height 3.270m  
 Min Body Ground Clearance 0.210m  
 Max Track Width 2.70m  
 Lock-to-lock time 3.00s  
 Curb to Curb Turning Radius 6.550m





client: Marden Homes	title: Articulated HGV Swept Path 2 of 3	date: 01/10/2018	scale @ A3 1:500
project: Kelvedon Road Tiptree	status: Planning (not for construction)	drawn:	Revision
discipline: Transport Planning	project no: JTP 07718	chk'd: SAA	dwg no: DR3





9.4m



client: Marden Homes	title: Articulated HGV Swept Path 1 of 3	date: 01/10/2018	scale @ A3 1:500
project: Kelvedon Road Tiptree	status: Planning (not for construction)	drawn:	Revision
discipline: Transport Planning	project no: JTP 07718	chk'd: SAA	dwg no: DR3







**Appendix 4**  
**Illustrative Development Layout**



AS PROPOSED LAYOUT PLAN

**DAP** **KELVEDON ROAD**  
PROPOSED SITE LAYOUT  
TIPTREE  
COLCHESTER  
COS QLX  
MARDEN HOMES LTD.  
23.10.20 1:500@A1 Project#1432  
**300.00**  
www.daparchitecture.co.uk



## **Appendix 5**

### **TRICS Data**

Calculation Reference: AUDIT-757101-181004-1022

TRIP RATE CALCULATION SELECTION PARAMETERS:

Land Use : 03 - RESIDENTIAL  
 Category : A - HOUSES PRIVATELY OWNED  
 VEHICLES

Selected regions and areas:

02	SOUTH EAST	
	ES EAST SUSSEX	2 days
	HC HAMPSHIRE	1 days
	KC KENT	2 days
	SC SURREY	1 days
	WS WEST SUSSEX	2 days
03	SOUTH WEST	
	DV DEVON	2 days
04	EAST ANGLIA	
	NF NORFOLK	2 days
	SF SUFFOLK	1 days
05	EAST MIDLANDS	
	LN LINCOLNSHIRE	1 days
06	WEST MIDLANDS	
	SH SHROPSHIRE	2 days
	ST STAFFORDSHIRE	1 days
07	YORKSHIRE & NORTH LINCOLNSHIRE	
	NE NORTH EAST LINCOLNSHIRE	1 days
	NY NORTH YORKSHIRE	6 days
08	NORTH WEST	
	CH CHESHIRE	2 days
09	NORTH	
	DH DURHAM	1 days
10	WALES	
	PS POWYS	1 days
11	SCOTLAND	
	AG ANGUS	1 days
	FA FALKIRK	1 days
	HI HIGHLAND	1 days
	PK PERTH & KINROSS	1 days

*This section displays the number of survey days per TRICS® sub-region in the selected set*

Secondary Filtering selection:

*This data displays the chosen trip rate parameter and its selected range. Only sites that fall within the parameter range are included in the trip rate calculation.*

Parameter: Number of dwellings  
 Actual Range: 7 to 805 (units: )  
 Range Selected by User: 5 to 4334 (units: )

Public Transport Provision:

Selection by: Include all surveys

Date Range: 01/01/10 to 19/04/18

*This data displays the range of survey dates selected. Only surveys that were conducted within this date range are included in the trip rate calculation.*

Selected survey days:

Monday	6 days
Tuesday	7 days
Wednesday	8 days
Thursday	7 days
Friday	4 days

*This data displays the number of selected surveys by day of the week.*

Selected survey types:

Manual count	32 days
Directional ATC Count	0 days

*This data displays the number of manual classified surveys and the number of unclassified ATC surveys, the total adding up to the overall number of surveys in the selected set. Manual surveys are undertaken using staff, whilst ATC surveys are undertaken using machines.*

Selected Locations:

Suburban Area (PPS6 Out of Centre)	16
Edge of Town	16

*This data displays the number of surveys per main location category within the selected set. The main location categories consist of Free Standing, Edge of Town, Suburban Area, Neighbourhood Centre, Edge of Town Centre, Town Centre and*

*This data displays the number of surveys per location sub-category within the selected set. The location sub-categories consist of Commercial Zone, Industrial Zone, Development Zone, Residential Zone, Retail Zone, Built-Up Zone, Village, Out of Town, High Street and No Sub Category.*

Secondary Filtering selection:

Use Class:

C3 32 days

*This data displays the number of surveys per Use Class classification within the selected set. The Use Classes Order 2005 has been used for this purpose, which can be found within the Library module of TRICS®.*

Population within 1 mile:

1,000 or Less	1 days
1,001 to 5,000	5 days
5,001 to 10,000	8 days
10,001 to 15,000	11 days
15,001 to 20,000	7 days

*This data displays the number of selected surveys within stated 1-mile radii of population.*

Population within 5 miles:

5,001 to 25,000	7 days
25,001 to 50,000	5 days
50,001 to 75,000	6 days
75,001 to 100,000	12 days
100,001 to 125,000	2 days

*This data displays the number of selected surveys within stated 5-mile radii of population.*

Car ownership within 5 miles:

0.6 to 1.0	8 days
1.1 to 1.5	24 days

*This data displays the number of selected surveys within stated ranges of average cars owned per residential dwelling, within a radius of 5-miles of selected survey sites.*

Travel Plan:

Yes	4 days
No	28 days

*This data displays the number of surveys within the selected set that were undertaken at sites with Travel Plans in place, and the number of surveys that were undertaken at sites without Travel Plans.*

PTAL Rating:

No PTAL Present	32 days
-----------------	---------

*This data displays the number of selected surveys with PTAL Ratings.*

LIST OF SITES relevant to selection parameters

1	AG-03-A-01 KEPTIE ROAD ARBROATH	BUNGALOWS/DET.	ANGUS
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 7 <i>Survey date: TUESDAY 22/05/12</i>		
2	CH-03-A-08 WHITCHURCH ROAD CHESTER BOUGHTON HEATH	DETACHED	CHESHIRE
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 11 <i>Survey date: TUESDAY 22/05/12</i>		
3	CH-03-A-09 GREYSTOKE ROAD MACCLESFIELD HURDSFIELD	TERRACED HOUSES	CHESHIRE
	Edge of Town Residential Zone Total Number of dwellings: 24 <i>Survey date: MONDAY 24/11/14</i>		
4	DH-03-A-01 GREENFIELDS ROAD BISHOP AUCKLAND	SEMI DETACHED	DURHAM
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 50 <i>Survey date: TUESDAY 28/03/17</i>		
5	DV-03-A-02 MILLHEAD ROAD HONITON	HOUSES & BUNGALOWS	DEVON
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 116 <i>Survey date: FRIDAY 25/09/15</i>		
6	DV-03-A-03 LOWER BRAND LANE HONITON	TERRACED & SEMI DETACHED	DEVON
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 70 <i>Survey date: MONDAY 28/09/15</i>		
7	ES-03-A-02 SOUTH COAST ROAD PEACEHAVEN	PRIVATE HOUSING	EAST SUSSEX
	Edge of Town Residential Zone Total Number of dwellings: 37 <i>Survey date: FRIDAY 18/11/11</i>		
8	ES-03-A-04 NEW LYDD ROAD CAMBER	MIXED HOUSES & FLATS	EAST SUSSEX
	Edge of Town Residential Zone Total Number of dwellings: 134 <i>Survey date: FRIDAY 15/07/16</i>		
9	FA-03-A-01 MANDELA AVENUE FALKIRK	SEMI -DETACHED/TERRACED	FALKIRK
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 37 <i>Survey date: THURSDAY 30/05/13</i>		

LIST OF SITES relevant to selection parameters (Cont.)

10	HC-03-A-19 CANADA WAY LIPHOOK	HOUSES & FLATS	HAMPSHIRE
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 62 <i>Survey date: MONDAY 27/11/17</i>		
11	HI-03-A-14 KING BRUDE ROAD INVERNESS SCORGUIE	SEMI-DETACHED & TERRACED	HIGHLAND
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 40 <i>Survey date: WEDNESDAY 23/03/16</i>		
12	KC-03-A-03 HYTHE ROAD ASHFORD WILLESBOROUGH	MIXED HOUSES & FLATS	KENT
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 51 <i>Survey date: THURSDAY 14/07/16</i>		
13	KC-03-A-07 RECVLVER ROAD HERNE BAY	MIXED HOUSES	KENT
	Edge of Town Residential Zone Total Number of dwellings: 288 <i>Survey date: WEDNESDAY 27/09/17</i>		
14	LN-03-A-03 ROOKERY LANE LINCOLN BOULTHAM	SEMI DETACHED	LINCOLNSHIRE
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 22 <i>Survey date: TUESDAY 18/09/12</i>		
15	NE-03-A-02 HANOVER WALK SCUNTHORPE	SEMI DETACHED & DETACHED	NORTH EAST LINCOLNSHIRE
	Edge of Town No Sub Category Total Number of dwellings: 432 <i>Survey date: MONDAY 12/05/14</i>		
16	NF-03-A-01 YARMOUTH ROAD CAISTER-ON-SEA	SEMI DET. & BUNGALOWS	NORFOLK
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 27 <i>Survey date: TUESDAY 16/10/12</i>		
17	NF-03-A-03 HALING WAY THETFORD	DETACHED HOUSES	NORFOLK
	Edge of Town Residential Zone Total Number of dwellings: 10 <i>Survey date: WEDNESDAY 16/09/15</i>		
18	NY-03-A-06 HORSEFAIR BOROUGHBRIDGE	BUNGALOWS & SEMI DET.	NORTH YORKSHIRE
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings: 115 <i>Survey date: FRIDAY 14/10/11</i>		

LIST OF SITES relevant to selection parameters (Cont.)

19	NY-03-A-07 CRAVEN WAY BOROUGHBRIDGE	DETACHED & SEMI DET.		NORTH YORKSHIRE
	Edge of Town No Sub Category Total Number of dwellings:		23	
	<i>Survey date: TUESDAY</i>		<i>18/10/11</i>	<i>Survey Type: MANUAL</i>
20	NY-03-A-09 GRAMMAR SCHOOL LANE NORTHALLERTON	MIXED HOUSING		NORTH YORKSHIRE
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings:		52	
	<i>Survey date: MONDAY</i>		<i>16/09/13</i>	<i>Survey Type: MANUAL</i>
21	NY-03-A-10 BOROUGHBRIDGE ROAD RIPON	HOUSES AND FLATS		NORTH YORKSHIRE
	Edge of Town No Sub Category Total Number of dwellings:		71	
	<i>Survey date: TUESDAY</i>		<i>17/09/13</i>	<i>Survey Type: MANUAL</i>
22	NY-03-A-11 HORSEFAIR BOROUGHBRIDGE	PRIVATE HOUSING		NORTH YORKSHIRE
	Edge of Town Residential Zone Total Number of dwellings:		23	
	<i>Survey date: WEDNESDAY</i>		<i>18/09/13</i>	<i>Survey Type: MANUAL</i>
23	NY-03-A-13 CATTERICK ROAD CATTERICK GARRISON OLD HOSPITAL COMPOUND	TERRACED HOUSES		NORTH YORKSHIRE
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings:		10	
	<i>Survey date: WEDNESDAY</i>		<i>10/05/17</i>	<i>Survey Type: MANUAL</i>
24	PK-03-A-01 TULLYLUMB TERRACE PERTH GORNHILL	DETAC. & BUNGALOWS		PERTH & KINROSS
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings:		36	
	<i>Survey date: WEDNESDAY</i>		<i>11/05/11</i>	<i>Survey Type: MANUAL</i>
25	PS-03-A-02 GUNROG ROAD WELSHPOOL	DETACHED/SEMI-DETACHED		POWYS
	Suburban Area (PPS6 Out of Centre) Residential Zone Total Number of dwellings:		28	
	<i>Survey date: MONDAY</i>		<i>11/05/15</i>	<i>Survey Type: MANUAL</i>
26	SC-03-A-04 HIGH ROAD BYFLEET	DETACHED & TERRACED		SURREY
	Edge of Town Residential Zone Total Number of dwellings:		71	
	<i>Survey date: THURSDAY</i>		<i>23/01/14</i>	<i>Survey Type: MANUAL</i>
27	SF-03-A-05 VALE LANE BURY ST EDMUNDS	DETACHED HOUSES		SUFFOLK
	Edge of Town Residential Zone Total Number of dwellings:		18	
	<i>Survey date: WEDNESDAY</i>		<i>09/09/15</i>	<i>Survey Type: MANUAL</i>



LIST OF SITES relevant to selection parameters (Cont.)

28	SH-03-A-05 SANDCROFT TELFORD SUTTON HILL Edge of Town Residential Zone Total Number of dwellings: <i>Survey date: THURSDAY</i>	SEMI -DETACHED/TERRACED      54 24/10/13	SHROPSHIRE       <i>Survey Type: MANUAL</i>
29	SH-03-A-06 ELLESMERE ROAD SHREWSBURY  Edge of Town Residential Zone Total Number of dwellings: <i>Survey date: THURSDAY</i>	BUNGALOWS      16 22/05/14	SHROPSHIRE       <i>Survey Type: MANUAL</i>
30	ST-03-A-07 BEACONSIDE STAFFORD MARSTON GATE Edge of Town Residential Zone Total Number of dwellings: <i>Survey date: WEDNESDAY</i>	DETACHED & SEMI -DETACHED      248 22/11/17	STAFFORDSHIRE       <i>Survey Type: MANUAL</i>
31	WS-03-A-04 HILLS FARM LANE HORSHAM BROADBRIDGE HEATH Edge of Town Residential Zone Total Number of dwellings: <i>Survey date: THURSDAY</i>	MIXED HOUSES      151 11/12/14	WEST SUSSEX       <i>Survey Type: MANUAL</i>
32	WS-03-A-06 ELLIS ROAD WEST HORSHAM S BROADBRIDGE HEATH Edge of Town Residential Zone Total Number of dwellings: <i>Survey date: THURSDAY</i>	MIXED HOUSES      805 02/03/17	WEST SUSSEX       <i>Survey Type: MANUAL</i>

*This section provides a list of all survey sites and days in the selected set. For each individual survey site, it displays a unique site reference code and site address, the selected trip rate calculation parameter and its value, the day of the week and date of each survey, and whether the survey was a manual classified count or an ATC count.*

TRIP RATE for Land Use 03 - RESIDENTIAL/A - HOUSES PRIVATELY OWNED  
 VEHICLES

Calculation factor: 1 DWELLS

BOLD print indicates peak (busiest) period

Time Range	ARRIVALS			DEPARTURES			TOTALS		
	No. Days	Ave. DWELLS	Trip Rate	No. Days	Ave. DWELLS	Trip Rate	No. Days	Ave. DWELLS	Trip Rate
00:00 - 01:00									
01:00 - 02:00									
02:00 - 03:00									
03:00 - 04:00									
04:00 - 05:00									
05:00 - 06:00									
06:00 - 07:00									
07:00 - 08:00	32	98	0.083	32	98	0.291	32	98	0.374
08:00 - 09:00	32	98	0.140	32	98	0.384	32	98	0.524
09:00 - 10:00	32	98	0.148	32	98	0.164	32	98	0.312
10:00 - 11:00	32	98	0.130	32	98	0.159	32	98	0.289
11:00 - 12:00	32	98	0.133	32	98	0.153	32	98	0.286
12:00 - 13:00	32	98	0.160	32	98	0.154	32	98	0.314
13:00 - 14:00	32	98	0.160	32	98	0.155	32	98	0.315
14:00 - 15:00	32	98	0.163	32	98	0.187	32	98	0.350
15:00 - 16:00	32	98	0.257	32	98	0.175	32	98	0.432
16:00 - 17:00	32	98	0.275	32	98	0.171	32	98	0.446
17:00 - 18:00	32	98	0.338	32	98	0.156	32	98	0.494
18:00 - 19:00	32	98	0.278	32	98	0.173	32	98	0.451
19:00 - 20:00									
20:00 - 21:00									
21:00 - 22:00									
22:00 - 23:00									
23:00 - 24:00									
<b>Total Rates:</b>			2.265			2.322			4.587

*This section displays the trip rate results based on the selected set of surveys and the selected count type (shown just above the table). It is split by three main columns, representing arrivals trips, departures trips, and total trips (arrivals plus departures). Within each of these main columns are three sub-columns. These display the number of survey days where count data is included (per time period), the average value of the selected trip rate calculation parameter (per time period), and the trip rate result (per time period). Total trip rates (the sum of the column) are also displayed at the foot of the table.*

*To obtain a trip rate, the average (mean) trip rate parameter value (TRP) is first calculated for all selected survey days that have count data available for the stated time period. The average (mean) number of arrivals, departures or totals (whichever applies) is also calculated (COUNT) for all selected survey days that have count data available for the stated time period. Then, the average count is divided by the average trip rate parameter value, and multiplied by the stated calculation factor (shown just above the table and abbreviated here as FACT). So, the method is: COUNT/TRP\*FACT. Trip rates are then rounded to 3 decimal places.*

The survey data, graphs and all associated supporting information, contained within the TRICS Database are published by TRICS Consortium Limited ("the Company") and the Company claims copyright and database rights in this published work. The Company authorises those who possess a current TRICS licence to access the TRICS Database and copy the data contained within the TRICS Database for the licence holders' use only. Any resulting copy must retain all copyrights and other proprietary notices, and any disclaimer contained thereon.

The Company accepts no responsibility for loss which may arise from reliance on data contained in the TRICS Database. [No warranty of any kind, express or implied, is made as to the data contained in the TRICS Database.]

#### Parameter summary

Trip rate parameter range selected:	7 - 805 (units: )
Survey date date range:	01/01/10 - 19/04/18
Number of weekdays (Monday-Friday):	32
Number of Saturdays:	0
Number of Sundays:	0
Surveys automatically removed from selection:	2
Surveys manually removed from selection:	0

*This section displays a quick summary of some of the data filtering selections made by the TRICS® user. The trip rate calculation parameter range of all selected surveys is displayed first, followed by the range of minimum and maximum survey dates selected by the user. Then, the total number of selected weekdays and weekend days in the selected set of surveys are shown. Finally, the number of survey days that have been manually removed from the selected set outside of the standard filtering procedure are displayed.*



**Appendix 6**  
**Census Information**

## WU03EW - Location of usual residence and place of work by method of travel to work (MSOA level)

ONS Crown Copyright Reserved [from Nomis on 28 January 2019]

population All usual residents aged 16 and over in employment the week before the census  
units Persons  
date 2011  
method of travel to work Driving a car or van

<b>place of work : 2011 census merged local authority district</b>	<b>usual residence E02004525 : Colchester 020</b>
Babergh	25
Basildon	47
Bedford	1
Braintree	332
Breckland	1
Brentwood	23
Broxbourne	1
Cambridge	3
Castle Point	3
Chelmsford	214
Colchester	472
East Hertfordshire	4
Epping Forest	8
Forest Heath	1
Harlow	12
Hertsmere	2
Ipswich	21
Maldon	330
Mid Suffolk	5
Norwich	1
Rochford	5


South Cambridgeshire	3
Southend-on-Sea	7
St Albans	2
St Edmundsbury	7
Stevenage	2
Suffolk Coastal	5
Tendring	68
Three Rivers	1
Thurrock	14
Uttlesford	21
Welwyn Hatfield	1
	1,642



## **Appendix 7**


### **Traffic Data**


Select Period 0800 Hourly Total








Select Period 1700 Hourly Total























**Appendix 8**  
**Network Flows**







Drawing Title	AM Peak 08:00-09:00 2019 Surveyed Flows	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 1	




Drawing Title	PM Peak 17:00-18:00 2019 Surveyed Flows	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 2	





Level Area      Local Growth Figure  
 E02004525      Colchester 020    1.080

Drawing Title	AM Peak 08:00-09:00 2025 Forecast Flows	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 3	





Level Area Local Growth Figure  
 E02004525 Colchester 020 1.079


Drawing Title	PM Peak 17:00-18:00 2025 Forecast Flows	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 4	





Drawing Title	AM Peak 08:00-09:00 Committed Development	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 5	



Drawing Title	PM Peak 17:00-18:00 Committed Development	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 6	




Drawing Title	AM Peak 08:00-09:00 2025 Base Flows	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 7	





Drawing Title	PM Peak 17:00-18:00 2025 Base Flows	Drawn	SAA
		Date	02/01/2019
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 8










Drawing Title	AM Peak 08:00-09:00 Residential Trip Distribution	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 9	





Drawing Title	PM Peak 17:00-18:00 Residential Trip Distribution	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 10	





Arrivals 18  
 Departures 50


Drawing Title	AM Peak 08:00-09:00 Residential Trip Generation	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 11	




Drawing Title	PM Peak 17:00-18:00 Residential Trip Generation	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 12	



Drawing Title	AM Peak 08:00-09:00 2025 Total Trips	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 13	



Drawing Title	PM Peak 17:00-18:00 2025 Total Trips	Drawn	SAA	
		Date	02/01/2019	
Project Title	Land to the South of Kelvedon Road, Tiptree	Ref	Figure 14	



**Appendix 9**  
**Junctions 9 Output**

<b>Junctions 9</b>
<b>ARCADY 9 - Roundabout Module</b>
Version: 9.5.1.7462 © Copyright TRL Limited, 2019
For sales and distribution information, program advice and maintenance, contact TRL: +44 (0)1344 379777 software@trl.co.uk www.trlsoftware.co.uk
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: Site Access.j9

Path: C:\Users\PC\OneDrive\Journey\Projects\004 Xero or Paid\2018\18\_099 Kelvedon Road Tiptree Phase 2\05 Calculations

Report generation date: 05/11/2020 17:21:25

- »2025 Total Development, AM
- »2025 Total Development, PM

**Summary of junction performance**

AM							PM							
Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity		Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity		
2025 Total Development														
Arm 1	D1	2.4	14.30	0.69	B	28 %	D2	0.5	6.64	0.32	A	7 %		
Arm 2		0.2	11.05	0.13	B			[Arm 1]	0.0	6.61	0.04		A	[Arm 3]
Arm 3		0.6	6.37	0.36	A				5.2	23.90	0.83		C	

There are warnings associated with one or more model runs - see the 'Data Errors and Warnings' tables for each Analysis or Demand Set.

Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle. Network Residual Capacity indicates the amount by which network flow could be increased before a user-definable threshold (see Analysis Options) is met.

**File summary**

**File Description**

Title	(untitled)
Location	
Site number	
Date	29/01/2019
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	
Enumerator	STEVE-PC\Steve
Description	

**Units**

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin

**Analysis Options**

Mini-roundabout model	Vehicle length (m)	Calculate Queue Percentiles	Calculate detailed queueing delay	Calculate residual capacity	Residual capacity criteria type	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)
JUNCTIONS 9	5.75			✓	Delay	0.85	36.00	20.00



### Demand Set Summary

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 Total Development	AM	ONE HOUR	07:45	09:15	15	✓
D2	2025 Total Development	PM	ONE HOUR	16:45	18:15	15	✓

### Analysis Set Details

ID	Include in report	Network flow scaling factor (%)	Network capacity scaling factor (%)
A1	✓	100.000	100.000

# 2025 Total Development, AM

## Data Errors and Warnings

Severity	Area	Item	Description
Warning	Mini-roundabout		Mini-roundabout appears to have unbalanced flows and may behave like a priority junction; treat results with caution. See User Guide for details.[Arms 1 and 3 have 94% of the total flow for the roundabout for one or more time segments]

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	untitled	Mini-roundabout		1, 2, 3	11.43	B

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		28	Arm 1

## Arms

### Arms

Arm	Name	Description
1	Kelvedon Road South East	
2	Site Access	
3	Kelvedon Road North West	

### Mini Roundabout Geometry

Arm	Approach road half-width (m)	Minimum approach road half-width (m)	Entry width (m)	Effective flare length (m)	Distance to next arm (m)	Entry corner kerb line distance (m)	Gradient over 50m (%)	Kerbed central island
1	3.00	3.00	4.70	1.0	12.00	7.00	0.0	
2	3.00	3.00	5.20	2.0	11.00	7.00	0.0	
3	3.00	3.00	4.50	2.0	18.00	16.00	0.0	

### Slope / Intercept / Capacity

#### Roundabout Slope and Intercept used in model

Arm	Final slope	Final intercept (PCU/hr)
1	0.600	900
2	0.609	784
3	0.648	981

The slope and intercept shown above include any corrections and adjustments.

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 Total Development	AM	ONE HOUR	07:45	09:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	560	100.000
2		ONE HOUR	✓	50	100.000
3		ONE HOUR	✓	314	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	7	553
	2	19	0	31
	3	303	11	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.69	14.30	2.4	B	514	771
2	0.13	11.05	0.2	B	46	69
3	0.36	6.37	0.6	A	288	432

### Main Results for each time segment

#### 07:45 - 08:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	422	105	8	895	0.471	418	241	0.0	1.0	8.231	A
2	38	9	413	533	0.071	37	13	0.0	0.1	7.989	A
3	236	59	14	972	0.243	235	436	0.0	0.4	5.365	A

#### 08:00 - 08:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	503	126	10	894	0.563	502	289	1.0	1.4	10.047	B
2	45	11	495	482	0.093	45	16	0.1	0.1	9.052	A
3	282	71	17	970	0.291	282	523	0.4	0.4	5.753	A

**08:15 - 08:30**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	617	154	12	893	0.691	613	354	1.4	2.3	13.942	B
2	55	14	605	415	0.133	55	20	0.1	0.2	10.973	B
3	346	86	21	967	0.357	345	639	0.4	0.6	6.355	A

**08:30 - 08:45**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	617	154	12	893	0.691	616	355	2.3	2.4	14.296	B
2	55	14	609	413	0.133	55	20	0.2	0.2	11.053	B
3	346	86	21	967	0.357	346	643	0.6	0.6	6.368	A

**08:45 - 09:00**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	503	126	10	894	0.563	507	290	2.4	1.5	10.332	B
2	45	11	501	479	0.094	45	16	0.2	0.1	9.135	A
3	282	71	17	970	0.291	283	529	0.6	0.5	5.771	A

**09:00 - 09:15**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	422	105	8	895	0.471	423	243	1.5	1.0	8.429	A
2	38	9	418	529	0.071	38	14	0.1	0.1	8.059	A
3	236	59	14	972	0.243	237	442	0.5	0.4	5.393	A

# 2025 Total Development, PM

## Data Errors and Warnings

Severity	Area	Item	Description
Warning	Mini-roundabout		Mini-roundabout appears to have unbalanced flows and may behave like a priority junction; treat results with caution. See User Guide for details.[Arms 1 and 3 have 98% of the total flow for the roundabout for one or more time segments]

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	untitled	Mini-roundabout		1, 2, 3	19.16	C

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		7	Arm 3

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D2	2025 Total Development	PM	ONE HOUR	16:45	18:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	260	100.000
2		ONE HOUR	✓	20	100.000
3		ONE HOUR	✓	739	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	17	243
	2	8	0	12
	3	712	27	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.32	6.64	0.5	A	239	358
2	0.04	6.61	0.0	A	18	28
3	0.83	23.90	5.2	C	678	1017

### Main Results for each time segment

#### 16:45 - 17:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	196	49	20	888	0.220	195	537	0.0	0.3	5.699	A
2	15	4	182	673	0.022	15	33	0.0	0.0	6.015	A
3	556	139	6	977	0.569	551	191	0.0	1.4	9.170	A

#### 17:00 - 17:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	234	58	24	886	0.264	233	644	0.3	0.4	6.069	A
2	18	4	218	651	0.028	18	39	0.0	0.0	6.254	A
3	664	166	7	976	0.680	661	229	1.4	2.3	12.422	B

#### 17:15 - 17:30

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	286	72	29	882	0.324	286	783	0.4	0.5	6.631	A
2	22	6	267	621	0.035	22	48	0.0	0.0	6.607	A
3	814	203	9	975	0.834	803	280	2.3	4.9	21.760	C

#### 17:30 - 17:45

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	286	72	30	882	0.324	286	792	0.5	0.5	6.643	A
2	22	6	268	621	0.035	22	48	0.0	0.0	6.610	A
3	814	203	9	975	0.834	812	281	4.9	5.2	23.897	C

#### 17:45 - 18:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	234	58	25	885	0.264	234	658	0.5	0.4	6.089	A
2	18	4	219	651	0.028	18	40	0.0	0.0	6.261	A
3	664	166	7	976	0.680	675	230	5.2	2.4	13.589	B

18:00 - 18:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	196	49	20	888	0.220	196	546	0.4	0.3	5.729	A
2	15	4	183	672	0.022	15	33	0.0	0.0	6.024	A
3	556	139	6	977	0.569	560	192	2.4	1.5	9.583	A

<b>Junctions 9</b>
<b>PICADY 9 - Priority Intersection Module</b>
Version: 9.5.1.7462 © Copyright TRL Limited, 2019
For sales and distribution information, program advice and maintenance, contact TRL: +44 (0)1344 379777 software@trl.co.uk www.trlsoftware.co.uk
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: Oak Road Maypole Road.j9

Path: C:\Users\PC\OneDrive\Journey\Projects\004 Xero or Paid\2018\18\_099 Kelvedon Road Tiptree Phase 2\05 Calculations

Report generation date: 05/11/2020 17:17:21

- »2025 With Development, AM
- »2025 With Development, PM

### Summary of junction performance

	AM						PM					
	Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity	Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity
2025 With Development												
Stream B-AC	D1	0.3	12.45	0.20	B	78 %	D2	0.5	12.95	0.32	B	69 %
Stream C-AB		0.3	8.31	0.20	A	[Stream B-AC]		0.0	8.52	0.04	A	[Stream B-AC]

Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle. Network Residual Capacity indicates the amount by which network flow could be increased before a user-definable threshold (see Analysis Options) is met.

### File summary

#### File Description

Title	(untitled)
Location	
Site number	
Date	28/01/2019
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	
Enumerator	STEVE-PC\Steve
Description	

### Units

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin

### Analysis Options

Vehicle length (m)	Calculate Queue Percentiles	Calculate detailed queueing delay	Calculate residual capacity	Residual capacity criteria type	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)
5.75			✓	Delay	0.85	36.00	20.00



### Demand Set Summary

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 With Development	AM	ONE HOUR	07:45	09:15	15	✓
D2	2025 With Development	PM	ONE HOUR	16:45	18:15	15	✓

### Analysis Set Details

ID	Include in report	Network flow scaling factor (%)	Network capacity scaling factor (%)
A1	✓	100.000	100.000

# 2025 With Development, AM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Maypole Road Oak Road	T-Junction	Two-way		1.93	A

### Junction Network Options

Driving side	Lighting	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	78	Stream B-AC

## Arms

### Arms

Arm	Name	Description	Arm type
A	Maypole Rd S		Major
B	Oak Road		Minor
C	Colchester Road		Major

### Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Has right turn bay	Visibility for right turn (m)	Blocks?	Blocking queue (PCU)
C	6.00			0.0	✓	1.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

### Minor Arm Geometry

Arm	Minor arm type	Lane width (m)	Visibility to left (m)	Visibility to right (m)
B	One lane	3.00	25	25

## Slope / Intercept / Capacity

### Priority Intersection Slopes and Intercepts

Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
B-A	498	0.091	0.229	0.144	0.328
B-C	640	0.098	0.248	-	-
C-B	574	0.222	0.222	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 With Development	AM	ONE HOUR	07:45	09:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	338	100.000
B		ONE HOUR	✓	73	100.000
C		ONE HOUR	✓	497	100.000

## Origin-Destination Data

### Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	14	324
	B	38	0	35
	C	409	88	0

## Vehicle Mix

### Heavy Vehicle Percentages

	To			
	A	B	C	
From	A	0	10	10
	B	10	0	10
	C	10	10	0

## Results

### Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.20	12.45	0.3	B	67	100
C-AB	0.20	8.31	0.3	A	93	140
C-A					363	544
A-B					13	19
A-C					297	446

### Main Results for each time segment

#### 07:45 - 08:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	55	14	451	0.122	54	0.0	0.2	9.969	A
C-AB	72	18	565	0.128	72	0.0	0.2	8.018	A
C-A	302	75			302				
A-B	11	3			11				
A-C	244	61			244				

**08:00 - 08:15**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	66	16	429	0.153	65	0.2	0.2	10.881	B
C-AB	90	22	574	0.156	90	0.2	0.2	8.167	A
C-A	357	89			357				
A-B	13	3			13				
A-C	291	73			291				

**08:15 - 08:30**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	80	20	398	0.202	80	0.2	0.3	12.425	B
C-AB	117	29	594	0.197	117	0.2	0.3	8.297	A
C-A	430	108			430				
A-B	15	4			15				
A-C	357	89			357				

**08:30 - 08:45**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	80	20	398	0.202	80	0.3	0.3	12.453	B
C-AB	117	29	594	0.197	117	0.3	0.3	8.310	A
C-A	430	108			430				
A-B	15	4			15				
A-C	357	89			357				

**08:45 - 09:00**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	66	16	429	0.153	66	0.3	0.2	10.916	B
C-AB	90	22	574	0.156	90	0.3	0.2	8.186	A
C-A	357	89			357				
A-B	13	3			13				
A-C	291	73			291				

**09:00 - 09:15**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	55	14	451	0.122	55	0.2	0.2	10.013	B
C-AB	72	18	565	0.128	73	0.2	0.2	8.048	A
C-A	302	75			302				
A-B	11	3			11				
A-C	244	61			244				

# 2025 With Development, PM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Maypole Road Oak Road	T-Junction	Two-way		2.19	A

### Junction Network Options

Driving side	Lighting	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	69	Stream B-AC

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D2	2025 With Development	PM	ONE HOUR	16:45	18:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	431	100.000
B		ONE HOUR	✓	129	100.000
C		ONE HOUR	✓	263	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		A	B	C
From	A	0	23	408
	B	44	0	85
	C	248	15	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		A	B	C
From	A	0	10	10
	B	10	0	10
	C	10	10	0

## Results

### Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.32	12.95	0.5	B	118	178
C-AB	0.04	8.52	0.0	A	14	21
C-A					227	341
A-B					21	32
A-C					374	562

### Main Results for each time segment

#### 16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	97	24	491	0.198	96	0.0	0.3	9.993	A
C-AB	11	3	508	0.023	11	0.0	0.0	7.974	A
C-A	187	47			187				
A-B	17	4			17				
A-C	307	77			307				

#### 17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	116	29	473	0.245	116	0.3	0.4	11.069	B
C-AB	14	3	496	0.028	14	0.0	0.0	8.204	A
C-A	223	56			223				
A-B	21	5			21				
A-C	367	92			367				

#### 17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	142	36	448	0.317	141	0.4	0.5	12.902	B
C-AB	17	4	481	0.035	17	0.0	0.0	8.524	A
C-A	273	68			273				
A-B	25	6			25				
A-C	449	112			449				

#### 17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	142	36	448	0.317	142	0.5	0.5	12.951	B
C-AB	17	4	481	0.035	17	0.0	0.0	8.524	A
C-A	273	68			273				
A-B	25	6			25				
A-C	449	112			449				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	116	29	473	0.245	117	0.5	0.4	11.126	B
C-AB	14	3	496	0.028	14	0.0	0.0	8.206	A
C-A	223	56			223				
A-B	21	5			21				
A-C	367	92			367				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	97	24	491	0.198	97	0.4	0.3	10.066	B
C-AB	11	3	508	0.023	11	0.0	0.0	7.981	A
C-A	187	47			187				
A-B	17	4			17				
A-C	307	77			307				

Junctions 9
PICADY 9 - Priority Intersection Module
Version: 9.5.1.7462 © Copyright TRL Limited, 2019
For sales and distribution information, program advice and maintenance, contact TRL: +44 (0)1344 379777 software@trl.co.uk www.trlsoftware.co.uk
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: Oak Road Kelvedon Road.j9

Path: C:\Users\PC\OneDrive\Journey\Projects\004 Xero or Paid\2018\18\_099 Kelvedon Road Tiptree Phase 2\05 Calculations

Report generation date: 05/11/2020 17:13:28

- »2025 With Development, AM
- »2025 With Development, PM

### Summary of junction performance

	AM						PM					
	Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity	Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity
2025 With Development												
Stream B-AC	D1	0.6	17.42	0.37	C	42 %	D2	0.1	13.84	0.09	B	77 %
Stream C-AB		0.0	7.24	0.01	A	[Stream B-AC]		0.0	9.02	0.02	A	[Stream B-AC]

*Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle. Network Residual Capacity indicates the amount by which network flow could be increased before a user-definable threshold (see Analysis Options) is met.*

### File summary

#### File Description

Title	(untitled)
Location	
Site number	
Date	28/01/2019
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	
Enumerator	STEVE-PC\Steve
Description	

### Units

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin

### Analysis Options

Vehicle length (m)	Calculate Queue Percentiles	Calculate detailed queueing delay	Calculate residual capacity	Residual capacity criteria type	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)
5.75			✓	Delay	0.85	36.00	20.00



### Demand Set Summary

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 With Development	AM	ONE HOUR	07:45	09:15	15	✓
D2	2025 With Development	PM	ONE HOUR	16:45	18:15	15	✓

### Analysis Set Details

ID	Include in report	Network flow scaling factor (%)	Network capacity scaling factor (%)
A1	✓	100.000	100.000

# 2025 With Development, AM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Maypole Road Oak Road	T-Junction	Two-way		2.33	A

### Junction Network Options

Driving side	Lighting	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	42	Stream B-AC

## Arms

### Arms

Arm	Name	Description	Arm type
A	Kelvedon Road W		Major
B	Oak Road		Minor
C	Kelvedon Road E		Major

### Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Has right turn bay	Visibility for right turn (m)	Blocks?	Blocking queue (PCU)
C	6.00			100.0	✓	1.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

### Minor Arm Geometry

Arm	Minor arm type	Lane width (m)	Visibility to left (m)	Visibility to right (m)
B	One lane	3.00	10	10

## Slope / Intercept / Capacity

### Priority Intersection Slopes and Intercepts

Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
B-A	486	0.088	0.224	0.141	0.320
B-C	630	0.097	0.244	-	-
C-B	632	0.245	0.245	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 With Development	AM	ONE HOUR	07:45	09:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	323	100.000
B		ONE HOUR	✓	119	100.000
C		ONE HOUR	✓	464	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		A	B	C
From	A	0	35	288
	B	102	0	17
	C	459	5	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		A	B	C
From	A	0	10	10
	B	10	0	10
	C	10	10	0

## Results

### Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.37	17.42	0.6	C	109	164
C-AB	0.01	7.24	0.0	A	5	7
C-A					421	632
A-B					32	48
A-C					264	396

### Main Results for each time segment

#### 07:45 - 08:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	90	22	404	0.222	88	0.0	0.3	12.488	B
C-AB	4	0.95	576	0.007	4	0.0	0.0	6.920	A
C-A	346	86			346				
A-B	26	7			26				
A-C	217	54			217				

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	107	27	385	0.278	107	0.3	0.4	14.198	B
C-AB	5	1	566	0.008	5	0.0	0.0	7.053	A
C-A	413	103			413				
A-B	31	8			31				
A-C	259	65			259				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	131	33	358	0.366	130	0.4	0.6	17.300	C
C-AB	6	1	553	0.010	6	0.0	0.0	7.238	A
C-A	505	126			505				
A-B	39	10			39				
A-C	317	79			317				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	131	33	358	0.366	131	0.6	0.6	17.416	C
C-AB	6	1	553	0.010	6	0.0	0.0	7.238	A
C-A	505	126			505				
A-B	39	10			39				
A-C	317	79			317				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	107	27	385	0.278	108	0.6	0.4	14.325	B
C-AB	5	1	566	0.008	5	0.0	0.0	7.056	A
C-A	413	103			413				
A-B	31	8			31				
A-C	259	65			259				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	90	22	404	0.222	90	0.4	0.3	12.621	B
C-AB	4	0.95	576	0.007	4	0.0	0.0	6.923	A
C-A	346	86			346				
A-B	26	7			26				
A-C	217	54			217				

# 2025 With Development, PM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Maypole Road Oak Road	T-Junction	Two-way		0.42	A

### Junction Network Options

Driving side	Lighting	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	77	Stream B-AC

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D2	2025 With Development	PM	ONE HOUR	16:45	18:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	712	100.000
B		ONE HOUR	✓	26	100.000
C		ONE HOUR	✓	241	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		A	B	C
From	A	0	138	574
	B	21	0	5
	C	235	6	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		A	B	C
From	A	0	10	10
	B	10	0	10
	C	10	10	0

## Results

### Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.09	13.84	0.1	B	24	36
C-AB	0.02	9.02	0.0	A	6	8
C-A					216	323
A-B					127	190
A-C					527	790

### Main Results for each time segment

#### 16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	20	5	376	0.052	19	0.0	0.1	11.087	B
C-AB	5	1	503	0.009	4	0.0	0.0	7.942	A
C-A	177	44			177				
A-B	104	26			104				
A-C	432	108			432				

#### 17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	23	6	350	0.067	23	0.1	0.1	12.100	B
C-AB	5	1	479	0.011	5	0.0	0.0	8.365	A
C-A	211	53			211				
A-B	124	31			124				
A-C	516	129			516				

#### 17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	29	7	315	0.091	29	0.1	0.1	13.833	B
C-AB	7	2	446	0.015	7	0.0	0.0	9.021	A
C-A	259	65			259				
A-B	152	38			152				
A-C	632	158			632				

#### 17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	29	7	315	0.091	29	0.1	0.1	13.844	B
C-AB	7	2	446	0.015	7	0.0	0.0	9.022	A
C-A	259	65			259				
A-B	152	38			152				
A-C	632	158			632				

**17:45 - 18:00**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	23	6	350	0.067	23	0.1	0.1	12.114	B
C-AB	5	1	479	0.011	5	0.0	0.0	8.366	A
C-A	211	53			211				
A-B	124	31			124				
A-C	516	129			516				

**18:00 - 18:15**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	20	5	376	0.052	20	0.1	0.1	11.105	B
C-AB	5	1	503	0.009	5	0.0	0.0	7.943	A
C-A	177	44			177				
A-B	104	26			104				
A-C	432	108			432				

Junctions 9
ARCADY 9 - Roundabout Module
Version: 9.5.1.7462 © Copyright TRL Limited, 2019
For sales and distribution information, program advice and maintenance, contact TRL: +44 (0)1344 379777 software@trl.co.uk www.trlsoftware.co.uk
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: Double Mini South.j9  
 Path: C:\Users\PC\OneDrive\Journey\Projects\004 Xero or Paid\2018\18\_099 Kelvedon Road Tiptree Phase 2\05 Calculations  
 Report generation date: 05/11/2020 17:08:45

- »2025 Base, AM
- »2025 Base, PM
- »2025 with development, AM
- »2025 with development, PM

**Summary of junction performance**

		AM						PM					
	Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity	Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity	
2025 Base													
Arm 1	D1	1.7	9.50	0.61	A	8 % [Arm 3]	D2	5.3	22.94	0.84	C	7 % [Arm 1]	
Arm 2		1.9	14.17	0.64	B			1.2	10.48	0.52	B		
Arm 3		3.7	22.12	0.78	C			3.9	21.43	0.79	C		
2025 with development													
Arm 1	D3	1.9	10.00	0.63	A	7 % [Arm 3]	D4	5.5	23.94	0.84	C	6 % [Arm 1]	
Arm 2		2.0	14.83	0.65	B			1.2	10.60	0.52	B		
Arm 3		3.9	23.08	0.79	C			4.4	23.73	0.81	C		

Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle. Network Residual Capacity indicates the amount by which network flow could be increased before a user-definable threshold (see Analysis Options) is met.

**File summary**

**File Description**

Title	(untitled)
Location	
Site number	
Date	29/01/2019
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	
Enumerator	STEVE-PC\Steve
Description	

**Units**

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin



### Analysis Options

Mini-roundabout model	Vehicle length (m)	Calculate Queue Percentiles	Calculate detailed queueing delay	Calculate residual capacity	Residual capacity criteria type	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)
JUNCTIONS 9	5.75			✓	Delay	0.85	36.00	20.00

### Demand Set Summary

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 Base	AM	ONE HOUR	07:45	09:15	15	✓
D2	2025 Base	PM	ONE HOUR	16:45	18:15	15	✓
D3	2025 with development	AM	ONE HOUR	07:45	09:15	15	✓
D4	2025 with development	PM	ONE HOUR	16:45	18:15	15	✓

### Analysis Set Details

ID	Include in report	Network flow scaling factor (%)	Network capacity scaling factor (%)
A1	✓	100.000	100.000

# 2025 Base, AM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Maypole Rd N Mini roundabout	Mini-roundabout		1, 2, 3	15.27	C

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		8	Arm 3

## Arms

### Arms

Arm	Name	Description
1	Link	
2	Kelvedon Road	
3	Maldon Road	

### Mini Roundabout Geometry

Arm	Approach road half-width (m)	Minimum approach road half-width (m)	Entry width (m)	Effective flare length (m)	Distance to next arm (m)	Entry corner kerb line distance (m)	Gradient over 50m (%)	Kerbed central island
1	3.00	3.00	4.50	6.0	5.00	3.00	0.0	
2	3.00	3.00	4.00	1.0	6.00	3.00	0.0	
3	3.00	3.00	4.00	3.0	5.00	3.00	0.0	

### Slope / Intercept / Capacity

#### Roundabout Slope and Intercept used in model

Arm	Final slope	Final intercept (PCU/hr)
1	0.622	1122
2	0.599	1031
3	0.608	1078

The slope and intercept shown above include any corrections and adjustments.

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 Base	AM	ONE HOUR	07:45	09:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	598	100.000
2		ONE HOUR	✓	448	100.000
3		ONE HOUR	✓	576	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	206	392
	2	399	0	49
	3	507	69	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.61	9.50	1.7	A	549	823
2	0.64	14.17	1.9	B	411	617
3	0.78	22.12	3.7	C	529	793

### Main Results for each time segment

#### 07:45 - 08:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	450	113	51	1090	0.413	447	676	0.0	0.8	6.139	A
2	337	84	293	855	0.394	334	205	0.0	0.7	7.567	A
3	434	108	298	897	0.484	430	330	0.0	1.0	8.410	A

#### 08:00 - 08:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	538	134	62	1084	0.496	536	811	0.8	1.1	7.217	A
2	403	101	352	820	0.491	401	247	0.7	1.0	9.429	A
3	518	129	358	860	0.602	515	396	1.0	1.6	11.399	B

**08:15 - 08:30**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	658	165	75	1076	0.612	656	988	1.1	1.7	9.379	A
2	493	123	430	773	0.638	490	301	1.0	1.9	13.827	B
3	634	159	436	812	0.781	626	484	1.6	3.6	20.481	C

**08:30 - 08:45**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	658	165	76	1075	0.612	658	997	1.7	1.7	9.497	A
2	493	123	432	772	0.639	493	303	1.9	1.9	14.171	B
3	634	159	439	811	0.782	633	485	3.6	3.7	22.124	C

**08:45 - 09:00**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	538	134	63	1083	0.496	540	824	1.7	1.1	7.324	A
2	403	101	354	819	0.492	406	249	1.9	1.1	9.673	A
3	518	129	362	858	0.604	526	398	3.7	1.7	12.205	B

**09:00 - 09:15**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	450	113	52	1090	0.413	451	686	1.1	0.8	6.216	A
2	337	84	296	853	0.395	339	208	1.1	0.7	7.717	A
3	434	108	302	894	0.485	436	333	1.7	1.1	8.699	A

# 2025 Base, PM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Maypole Rd N Mini roundabout	Mini-roundabout		1, 2, 3	19.83	C

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		7	Arm 1

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D2	2025 Base	PM	ONE HOUR	16:45	18:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	785	100.000
2		ONE HOUR	✓	368	100.000
3		ONE HOUR	✓	623	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	409	376
	2	313	0	55
	3	492	131	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.84	22.94	5.3	C	720	1080
2	0.52	10.48	1.2	B	338	507
3	0.79	21.43	3.9	C	572	858

### Main Results for each time segment

#### 16:45 - 17:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	591	148	98	1061	0.557	586	601	0.0	1.4	8.232	A
2	277	69	280	863	0.321	275	403	0.0	0.5	6.717	A
3	469	117	234	935	0.501	465	322	0.0	1.1	8.340	A

#### 17:00 - 17:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	706	176	117	1049	0.673	702	721	1.4	2.2	11.303	B
2	331	83	336	829	0.399	330	483	0.5	0.7	7.921	A
3	560	140	281	907	0.617	558	386	1.1	1.7	11.245	B

#### 17:15 - 17:30

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	864	216	143	1034	0.836	853	878	2.2	4.9	20.762	C
2	405	101	409	786	0.516	403	587	0.7	1.1	10.312	B
3	686	171	343	869	0.789	678	469	1.7	3.7	19.906	C

#### 17:30 - 17:45

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	864	216	144	1033	0.837	863	886	4.9	5.3	22.941	C
2	405	101	413	783	0.518	405	594	1.1	1.2	10.475	B
3	686	171	345	868	0.790	685	474	3.7	3.9	21.426	C

#### 17:45 - 18:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	706	176	120	1048	0.673	717	732	5.3	2.4	12.367	B
2	331	83	344	825	0.401	332	493	1.2	0.7	8.072	A
3	560	140	283	906	0.618	568	393	3.9	1.8	12.011	B

18:00 - 18:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	591	148	99	1061	0.557	595	609	2.4	1.4	8.571	A
2	277	69	285	860	0.322	278	409	0.7	0.5	6.816	A
3	469	117	236	934	0.502	472	326	1.8	1.1	8.620	A

# 2025 with development, AM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Maypole Rd N Mini roundabout	Mini-roundabout		1, 2, 3	15.94	C

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		7	Arm 3

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D3	2025 with development	AM	ONE HOUR	07:45	09:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	617	100.000
2		ONE HOUR	✓	448	100.000
3		ONE HOUR	✓	583	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	206	411
	2	399	0	49
	3	514	69	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0



## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.63	10.00	1.9	A	566	849
2	0.65	14.83	2.0	B	411	617
3	0.79	23.08	3.9	C	535	802

### Main Results for each time segment

#### 07:45 - 08:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	465	116	51	1090	0.426	461	681	0.0	0.8	6.266	A
2	337	84	307	847	0.398	334	205	0.0	0.7	7.690	A
3	439	110	298	897	0.490	435	344	0.0	1.0	8.501	A

#### 08:00 - 08:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	555	139	62	1084	0.512	553	817	0.8	1.1	7.447	A
2	403	101	369	810	0.497	401	246	0.7	1.1	9.661	A
3	524	131	357	860	0.609	522	413	1.0	1.7	11.602	B

#### 08:15 - 08:30

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	679	170	75	1076	0.632	677	995	1.1	1.8	9.852	A
2	493	123	451	761	0.648	490	301	1.1	1.9	14.431	B
3	642	160	436	812	0.790	634	504	1.7	3.7	21.208	C

#### 08:30 - 08:45

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	679	170	76	1075	0.632	679	1004	1.8	1.9	9.997	A
2	493	123	452	760	0.649	493	303	1.9	2.0	14.831	B
3	642	160	439	811	0.792	641	506	3.7	3.9	23.076	C

#### 08:45 - 09:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	555	139	63	1083	0.512	557	831	1.9	1.2	7.575	A
2	403	101	371	808	0.498	406	249	2.0	1.1	9.937	A
3	524	131	362	858	0.611	533	416	3.9	1.8	12.492	B

09:00 - 09:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	465	116	52	1090	0.426	466	691	1.2	0.8	6.364	A
2	337	84	310	845	0.399	339	208	1.1	0.7	7.850	A
3	439	110	302	894	0.491	442	347	1.8	1.1	8.806	A

# 2025 with development, PM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Maypole Rd N Mini roundabout	Mini-roundabout		1, 2, 3	21.14	C

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		6	Arm 1

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D4	2025 with development	PM	ONE HOUR	16:45	18:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	792	100.000
2		ONE HOUR	✓	368	100.000
3		ONE HOUR	✓	640	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	409	383
	2	313	0	55
	3	509	131	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.84	23.94	5.5	C	727	1090
2	0.52	10.60	1.2	B	338	507
3	0.81	23.73	4.4	C	587	881

### Main Results for each time segment

#### 16:45 - 17:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	596	149	98	1061	0.562	591	613	0.0	1.4	8.319	A
2	277	69	286	859	0.322	275	403	0.0	0.5	6.753	A
3	482	120	234	936	0.515	477	327	0.0	1.1	8.559	A

#### 17:00 - 17:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	712	178	117	1049	0.679	709	736	1.4	2.2	11.501	B
2	331	83	343	825	0.401	330	483	0.5	0.7	7.981	A
3	575	144	281	907	0.634	573	392	1.1	1.8	11.737	B

#### 17:15 - 17:30

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	872	218	142	1034	0.844	860	896	2.2	5.2	21.480	C
2	405	101	416	781	0.519	403	587	0.7	1.2	10.429	B
3	705	176	343	869	0.811	695	476	1.8	4.2	21.677	C

#### 17:30 - 17:45

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	872	218	144	1033	0.844	871	904	5.2	5.5	23.937	C
2	405	101	421	778	0.521	405	594	1.2	1.2	10.603	B
3	705	176	345	868	0.812	704	482	4.2	4.4	23.727	C

#### 17:45 - 18:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	712	178	120	1048	0.680	724	748	5.5	2.4	12.678	B
2	331	83	350	821	0.403	333	494	1.2	0.8	8.140	A
3	575	144	283	906	0.635	585	400	4.4	2.0	12.706	B

18:00 - 18:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	596	149	99	1060	0.562	600	622	2.4	1.4	8.676	A
2	277	69	290	857	0.323	278	409	0.8	0.5	6.854	A
3	482	120	236	934	0.516	485	332	2.0	1.2	8.881	A

Junctions 9
ARCADY 9 - Roundabout Module
Version: 9.5.1.7462 © Copyright TRL Limited, 2019
For sales and distribution information, program advice and maintenance, contact TRL: +44 (0)1344 379777 software@trl.co.uk www.trlsoftware.co.uk
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: Double Mini North.j9  
 Path: C:\Users\PC\OneDrive\Journey\Projects\004 Xero or Paid\2018\18\_099 Kelvedon Road Tiptree Phase 2\05 Calculations  
 Report generation date: 05/11/2020 16:59:36

- »2025 Base, AM
- »2025 Base, PM
- »2025 with development, AM
- »2025 with development, PM

**Summary of junction performance**

AM							PM					
Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity		Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity
2025 Base												
Arm 1	D1	1.2	8.05	0.53	A	-3 % [Arm 3]	D2	4.5	18.96	0.81	C	11 % [Arm 1]
Arm 2		0.6	5.93	0.36	A			2.2	13.92	0.68	B	
Arm 3		8.4	42.84	0.90	E			1.5	12.92	0.57	B	
2025 with development												
Arm 1	D3	1.3	8.18	0.54	A	-4 % [Arm 3]	D4	5.4	22.05	0.84	C	8 % [Arm 1]
Arm 2		0.7	6.12	0.38	A			2.3	14.30	0.69	B	
Arm 3		9.4	47.97	0.92	E			1.5	13.11	0.58	B	

Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle. Network Residual Capacity indicates the amount by which network flow could be increased before a user-definable threshold (see Analysis Options) is met.

**File summary**

**File Description**

Title	(untitled)
Location	
Site number	
Date	29/01/2019
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	
Enumerator	STEVE-PC\Steve
Description	

**Units**

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin

### Analysis Options

Mini-roundabout model	Vehicle length (m)	Calculate Queue Percentiles	Calculate detailed queueing delay	Calculate residual capacity	Residual capacity criteria type	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)
JUNCTIONS 9	5.75			✓	Delay	0.85	36.00	20.00

### Demand Set Summary

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 Base	AM	ONE HOUR	07:45	09:15	15	✓
D2	2025 Base	PM	ONE HOUR	16:45	18:15	15	✓
D3	2025 with development	AM	ONE HOUR	07:45	09:15	15	✓
D4	2025 with development	PM	ONE HOUR	16:45	18:15	15	✓

### Analysis Set Details

ID	Include in report	Network flow scaling factor (%)	Network capacity scaling factor (%)
A1	✓	100.000	100.000

# 2025 Base, AM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Maypole Rd N Mini roundabout	Mini-roundabout		1, 2, 3	23.13	C

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		-3	Arm 3

## Arms

### Arms

Arm	Name	Description
1	Link	
2	Kelvedon Road	
3	Maypole Road	

### Mini Roundabout Geometry

Arm	Approach road half-width (m)	Minimum approach road half-width (m)	Entry width (m)	Effective flare length (m)	Distance to next arm (m)	Entry corner kerb line distance (m)	Gradient over 50m (%)	Kerbed central island
1	3.00	3.00	4.50	6.0	5.00	3.00	0.0	
2	3.00	3.00	6.00	18.0	6.00	3.00	0.0	
3	3.00	3.00	3.30	1.0	8.00	3.00	0.0	

### Slope / Intercept / Capacity

#### Roundabout Slope and Intercept used in model

Arm	Final slope	Final intercept (PCU/hr)
1	0.622	1122
2	0.664	1292
3	0.596	1014

The slope and intercept shown above include any corrections and adjustments.

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 Base	AM	ONE HOUR	07:45	09:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00



### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	511	100.000
2		ONE HOUR	✓	338	100.000
3		ONE HOUR	✓	686	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	166	345
	2	272	0	66
	3	586	100	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.53	8.05	1.2	A	469	703
2	0.36	5.93	0.6	A	310	465
3	0.90	42.84	8.4	E	629	944

### Main Results for each time segment

#### 07:45 - 08:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	385	96	74	1076	0.358	382	640	0.0	0.6	5.690	A
2	254	64	258	1121	0.227	253	199	0.0	0.3	4.557	A
3	516	129	204	893	0.578	511	308	0.0	1.5	10.209	B

#### 08:00 - 08:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	459	115	89	1067	0.431	459	767	0.6	0.8	6.501	A
2	304	76	310	1087	0.280	303	238	0.3	0.4	5.053	A
3	617	154	244	869	0.710	612	369	1.5	2.6	15.182	C

**08:15 - 08:30**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	563	141	107	1055	0.533	561	928	0.8	1.2	7.980	A
2	372	93	379	1041	0.358	371	290	0.4	0.6	5.909	A
3	755	189	299	836	0.903	736	451	2.6	7.4	34.306	D

**08:30 - 08:45**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	563	141	110	1054	0.534	563	941	1.2	1.2	8.053	A
2	372	93	380	1040	0.358	372	292	0.6	0.6	5.927	A
3	755	189	299	836	0.904	751	452	7.4	8.4	42.836	E

**08:45 - 09:00**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	459	115	93	1064	0.432	461	791	1.2	0.8	6.580	A
2	304	76	311	1086	0.280	305	243	0.6	0.4	5.073	A
3	617	154	245	868	0.710	639	371	8.4	2.9	18.701	C

**09:00 - 09:15**

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	385	96	76	1075	0.358	386	651	0.8	0.6	5.751	A
2	254	64	260	1119	0.227	255	201	0.4	0.3	4.583	A
3	516	129	205	892	0.579	522	310	2.9	1.6	10.837	B

# 2025 Base, PM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Maypole Rd N Mini roundabout	Mini-roundabout		1, 2, 3	16.06	C

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		11	Arm 1

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D2	2025 Base	PM	ONE HOUR	16:45	18:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	806	100.000
2		ONE HOUR	✓	540	100.000
3		ONE HOUR	✓	374	100.000

## Origin-Destination Data

### Demand (PCU/hr)

	To			
	1	2	3	
From	1	0	239	567
	2	452	0	88
	3	332	42	0

## Vehicle Mix

### Heavy Vehicle Percentages

	To			
	1	2	3	
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.81	18.96	4.5	C	740	1109
2	0.68	13.92	2.2	B	496	743
3	0.57	12.92	1.5	B	343	515

### Main Results for each time segment

#### 16:45 - 17:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	607	152	31	1103	0.550	602	586	0.0	1.3	7.822	A
2	407	102	423	1011	0.402	404	210	0.0	0.7	6.485	A
3	282	70	338	813	0.346	279	489	0.0	0.6	7.389	A

#### 17:00 - 17:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	725	181	38	1099	0.659	722	703	1.3	2.1	10.413	B
2	485	121	508	955	0.508	484	252	0.7	1.1	8.375	A
3	336	84	405	773	0.435	335	586	0.6	0.8	9.024	A

#### 17:15 - 17:30

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	887	222	46	1094	0.811	878	858	2.1	4.3	17.689	C
2	595	149	618	882	0.674	590	306	1.1	2.2	13.386	B
3	412	103	494	720	0.572	409	714	0.8	1.4	12.656	B

#### 17:30 - 17:45

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	887	222	46	1093	0.812	887	863	4.3	4.5	18.958	C
2	595	149	624	878	0.677	594	309	2.2	2.2	13.924	B
3	412	103	497	718	0.574	412	721	1.4	1.5	12.920	B

#### 17:45 - 18:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	725	181	38	1099	0.660	734	710	4.5	2.2	11.112	B
2	485	121	516	950	0.511	490	256	2.2	1.2	8.691	A
3	336	84	410	770	0.437	339	596	1.5	0.9	9.228	A

18:00 - 18:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	607	152	32	1102	0.550	610	593	2.2	1.4	8.096	A
2	407	102	429	1007	0.404	408	213	1.2	0.8	6.627	A
3	282	70	342	811	0.347	283	496	0.9	0.6	7.514	A

# 2025 with development, AM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Maypole Rd N Mini roundabout	Mini-roundabout		1, 2, 3	25.20	D

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		-4	Arm 3

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D3	2025 with development	AM	ONE HOUR	07:45	09:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	518	100.000
2		ONE HOUR	✓	357	100.000
3		ONE HOUR	✓	686	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	173	345
	2	291	0	66
	3	586	100	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.54	8.18	1.3	A	475	713
2	0.38	6.12	0.7	A	328	491
3	0.92	47.97	9.4	E	629	944

### Main Results for each time segment

#### 07:45 - 08:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	390	97	74	1076	0.362	388	654	0.0	0.6	5.731	A
2	269	67	258	1121	0.240	267	204	0.0	0.3	4.631	A
3	516	129	218	884	0.584	510	308	0.0	1.5	10.431	B

#### 08:00 - 08:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	466	116	89	1067	0.437	465	784	0.6	0.8	6.569	A
2	321	80	310	1087	0.295	320	244	0.3	0.5	5.164	A
3	617	154	261	859	0.718	612	369	1.5	2.6	15.765	C

#### 08:15 - 08:30

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	570	143	107	1056	0.540	569	946	0.8	1.3	8.100	A
2	393	98	379	1041	0.378	392	297	0.5	0.7	6.098	A
3	755	189	320	824	0.917	734	451	2.6	8.1	37.171	E

#### 08:30 - 08:45

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	570	143	109	1054	0.541	570	961	1.3	1.3	8.179	A
2	393	98	380	1040	0.378	393	300	0.7	0.7	6.119	A
3	755	189	320	823	0.917	750	452	8.1	9.4	47.975	E

#### 08:45 - 09:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	466	116	94	1064	0.438	467	811	1.3	0.9	6.654	A
2	321	80	311	1086	0.296	322	250	0.7	0.5	5.190	A
3	617	154	262	858	0.719	642	371	9.4	3.0	20.207	C

09:00 - 09:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	390	97	76	1075	0.363	391	665	0.9	0.6	5.797	A
2	269	67	260	1119	0.240	269	207	0.5	0.3	4.659	A
3	516	129	219	884	0.585	522	310	3.0	1.6	11.120	B



# 2025 with development, PM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Maypole Rd N Mini roundabout	Mini-roundabout		1, 2, 3	17.73	C

### Junction Network Options

Driving side	Lighting	Road surface	In London	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	Normal/unknown		8	Arm 1

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D4	2025 with development	PM	ONE HOUR	16:45	18:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
1		ONE HOUR	✓	834	100.000
2		ONE HOUR	✓	547	100.000
3		ONE HOUR	✓	374	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To		
		1	2	3
From	1	0	267	567
	2	459	0	88
	3	332	42	0

## Vehicle Mix

### Heavy Vehicle Percentages

		To		
		1	2	3
From	1	0	10	10
	2	10	0	10
	3	10	10	0

## Results

### Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
1	0.84	22.05	5.4	C	765	1148
2	0.69	14.30	2.3	B	502	753
3	0.58	13.11	1.5	B	343	515

### Main Results for each time segment

#### 16:45 - 17:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	628	157	31	1103	0.569	622	591	0.0	1.4	8.148	A
2	412	103	423	1011	0.407	409	231	0.0	0.7	6.541	A
3	282	70	343	810	0.348	279	489	0.0	0.6	7.434	A

#### 17:00 - 17:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	750	187	38	1099	0.682	746	709	1.4	2.3	11.122	B
2	492	123	507	955	0.515	490	277	0.7	1.1	8.483	A
3	336	84	411	769	0.437	335	586	0.6	0.8	9.100	A

#### 17:15 - 17:30

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	918	230	46	1094	0.840	907	865	2.3	5.1	20.085	C
2	602	151	617	883	0.682	598	336	1.1	2.3	13.684	B
3	412	103	502	715	0.576	409	713	0.8	1.4	12.836	B

#### 17:30 - 17:45

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	918	230	46	1093	0.840	917	871	5.1	5.4	22.054	C
2	602	151	623	878	0.686	602	340	2.3	2.3	14.295	B
3	412	103	505	713	0.577	412	720	1.4	1.5	13.114	B

#### 17:45 - 18:00

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	750	187	38	1099	0.682	761	717	5.4	2.5	12.126	B
2	492	123	518	949	0.518	496	282	2.3	1.2	8.842	A
3	336	84	416	766	0.439	339	598	1.5	0.9	9.312	A

18:00 - 18:15

Arm	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Circulating flow (PCU/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Throughput (exit side) (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
1	628	157	32	1102	0.570	632	598	2.5	1.5	8.482	A
2	412	103	430	1007	0.409	414	234	1.2	0.8	6.693	A
3	282	70	347	808	0.349	283	496	0.9	0.6	7.560	A

<b>Junctions 9</b>
<b>PICADY 9 - Priority Intersection Module</b>
Version: 9.5.1.7462 © Copyright TRL Limited, 2019
For sales and distribution information, program advice and maintenance, contact TRL: +44 (0)1344 379777 software@trl.co.uk www.trlsoftware.co.uk
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: Townsend Stagger.j9  
 Path: C:\Users\PC\OneDrive\Journey\Projects\004 Xero or Paid\2018\18\_099 Kelvedon Road Tiptree Phase 2\05 Calculations  
 Report generation date: 05/11/2020 16:41:32

- »2025 With Development, AM
- »2025 With Development, PM

**Summary of junction performance**

	AM						PM					
	Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity	Set ID	Queue (PCU)	Delay (s)	RFC	LOS	Network Residual Capacity
2025 With Development												
Stream B-ACD	D1	0.4	14.94	0.29	B	49 % [Stream B-ACD]	D2	0.5	13.87	0.30	B	62 % [Stream B-ACD]
Stream AB-CD		0.2	7.52	0.11	A			0.2	9.37	0.16	A	
Stream D-ABC		0.3	10.63	0.19	B			0.1	10.24	0.07	B	
Stream CD-AB		0.2	8.76	0.12	A			0.1	7.27	0.09	A	

Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle. Network Residual Capacity indicates the amount by which network flow could be increased before a user-definable threshold (see Analysis Options) is met.

**File summary**

**File Description**

Title	(untitled)
Location	
Site number	
Date	28/01/2019
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	
Enumerator	STEVE-PC\Steve
Description	

**Units**

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin

**Analysis Options**

Vehicle length (m)	Calculate Queue Percentiles	Calculate detailed queueing delay	Calculate residual capacity	Residual capacity criteria type	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)
5.75			✓	Delay	0.85	36.00	20.00

### Demand Set Summary

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 With Development	AM	ONE HOUR	07:45	09:15	15	✓
D2	2025 With Development	PM	ONE HOUR	16:45	18:15	15	✓

### Analysis Set Details

ID	Include in report	Network flow scaling factor (%)	Network capacity scaling factor (%)
A1	✓	100.000	100.000

# 2025 With Development, AM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Kelvedon Rd Townsend Rd Stagger	Left-Right Stagger	Two-way		1.60	A

### Junction Network Options

Driving side	Lighting	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	49	Stream B-ACD

## Arms

### Arms

Arm	Name	Description	Arm type
A	Kelvedon Road E		Major
B	Grange Road		Minor
C	Kelvedon Road W		Major
D	Townsend Road		Minor

### Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Has right turn bay	Visibility for right turn (m)	Blocks?	Blocking queue (PCU)
A	6.00			50.0	✓	1.00
C	6.00			55.0	✓	1.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

### Minor Arm Geometry

Arm	Minor arm type	Lane width (m)	Visibility to left (m)	Visibility to right (m)
B	One lane	3.00	10	10
D	One lane	2.20	10	10

## Slope / Intercept / Capacity

### Priority Intersection Slopes and Intercepts

Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for A-D	Slope for B-C	Slope for B-D	Slope for C-A	Slope for C-B	Slope for C-D	Slope for D-A	Slope for D-B
AB-D	603	-	-	-	-	-	0.234	0.234	0.234	-	-
B-A	486	0.088	0.224	0.224	-	-	0.141	0.320	-	0.141	0.320
B-CD	630	0.097	0.244	0.244	-	-	-	-	-	-	-
CD-B	606	0.235	0.235	0.235	-	-	-	-	-	-	-
D-AB	580	-	-	-	-	-	0.225	0.225	0.089	-	-
D-C	447	-	0.129	0.294	0.129	0.294	0.206	0.206	0.081	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025 With Development	AM	ONE HOUR	07:45	09:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	574	100.000
B		ONE HOUR	✓	99	100.000
C		ONE HOUR	✓	326	100.000
D		ONE HOUR	✓	80	100.000

## Origin-Destination Data

### Demand (PCU/hr)

	From	To			
		A	B	C	D
	A	0	84	446	44
	B	43	0	46	10
	C	299	25	0	2
	D	48	23	9	0

## Vehicle Mix

### Heavy Vehicle Percentages

	From	To			
		A	B	C	D
	A	0	10	10	10
	B	10	0	10	10
	C	10	10	0	10
	D	10	10	10	0

## Results

### Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-ACD	0.29	14.94	0.4	B	91	136
A-B					77	116
A-C					409	614
A-D					40	61
AB-CD	0.11	7.52	0.2	A	55	82
AB-C					446	669
D-ABC	0.19	10.63	0.3	B	73	110
C-D					2	3
C-A					274	412
C-B					23	34
CD-AB	0.12	8.76	0.2	A	48	72
C-D-A					315	472

**Main Results for each time segment**

**07:45 - 08:00**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	75	19	434	0.172	74	0.0	0.2	10.950	B
A-B	63	16			63				
A-C	336	84			336				
A-D	33	8			33				
AB-CD	43	11	580	0.074	43	0.0	0.1	7.361	A
AB-C	367	92			367				
D-ABC	60	15	494	0.122	60	0.0	0.2	9.107	A
C-D	2	0.38			2				
C-A	225	56			225				
C-B	19	5			19				
CD-AB	38	9	528	0.071	37	0.0	0.1	8.065	A
CD-A	259	65			259				

**08:00 - 08:15**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	89	22	409	0.217	89	0.2	0.3	12.338	B
A-B	76	19			76				
A-C	401	100			401				
A-D	40	10			40				
AB-CD	53	13	584	0.091	53	0.1	0.1	7.452	A
AB-C	438	109			438				
D-ABC	72	18	480	0.150	72	0.2	0.2	9.694	A
C-D	2	0.45			2				
C-A	269	67			269				
C-B	22	6			22				
CD-AB	46	12	519	0.089	46	0.1	0.1	8.368	A
CD-A	309	77			309				

**08:15 - 08:30**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	109	27	374	0.291	108	0.3	0.4	14.877	B
A-B	92	23			92				
A-C	491	123			491				
A-D	48	12			48				
AB-CD	68	17	595	0.114	68	0.1	0.2	7.520	A
AB-C	533	133			533				
D-ABC	88	22	461	0.191	88	0.2	0.3	10.615	B
C-D	2	0.55			2				
C-A	329	82			329				
C-B	28	7			28				
CD-AB	59	15	511	0.115	59	0.1	0.2	8.754	A
CD-A	376	94			376				



08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	109	27	374	0.291	109	0.4	0.4	14.942	B
A-B	92	23			92				
A-C	491	123			491				
A-D	48	12			48				
AB-CD	68	17	595	0.115	68	0.2	0.2	7.525	A
AB-C	533	133			533				
D-ABC	88	22	461	0.191	88	0.3	0.3	10.630	B
C-D	2	0.55			2				
C-A	329	82			329				
C-B	28	7			28				
CD-AB	59	15	511	0.116	59	0.2	0.2	8.762	A
CD-A	376	94			376				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	89	22	409	0.218	90	0.4	0.3	12.412	B
A-B	76	19			76				
A-C	401	100			401				
A-D	40	10			40				
AB-CD	53	13	585	0.091	53	0.2	0.1	7.460	A
AB-C	438	110			438				
D-ABC	72	18	480	0.150	72	0.3	0.2	9.716	A
C-D	2	0.45			2				
C-A	269	67			269				
C-B	22	6			22				
CD-AB	46	12	519	0.089	46	0.2	0.1	8.379	A
CD-A	309	77			309				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	75	19	434	0.172	75	0.3	0.2	11.031	B
A-B	63	16			63				
A-C	336	84			336				
A-D	33	8			33				
AB-CD	43	11	581	0.075	43	0.1	0.1	7.375	A
AB-C	368	92			368				
D-ABC	60	15	494	0.122	60	0.2	0.2	9.141	A
C-D	2	0.38			2				
C-A	225	56			225				
C-B	19	5			19				
CD-AB	38	9	528	0.072	38	0.1	0.1	8.080	A
CD-A	260	65			260				

# 2025 With Development, PM

## Data Errors and Warnings

No errors or warnings

## Junction Network

### Junctions

Junction	Name	Junction type	Major road direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Kelvedon Rd Townsend Rd Stagger	Left-Right Stagger	Two-way		1.43	A

### Junction Network Options

Driving side	Lighting	Network residual capacity (%)	First arm reaching threshold
Left	Normal/unknown	62	Stream B-ACD

## Traffic Demand

### Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D2	2025 With Development	PM	ONE HOUR	16:45	18:15	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

### Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	290	100.000
B		ONE HOUR	✓	109	100.000
C		ONE HOUR	✓	593	100.000
D		ONE HOUR	✓	26	100.000

## Origin-Destination Data

### Demand (PCU/hr)

		To				
		A	B	C	D	
From	A	0	32	230	28	
	B	55	0	18	36	
	C	530	35	0	28	
	D	18	6	2	0	

## Vehicle Mix

### Heavy Vehicle Percentages

		To				
		A	B	C	D	
From	A	0	10	10	10	
	B	10	0	10	10	
	C	10	10	0	10	
	D	10	10	10	0	

## Results

### Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-ACD	0.30	13.87	0.5	B	100	150
A-B					29	44
A-C					211	317
A-D					26	39
AB-CD	0.16	9.37	0.2	A	63	95
AB-C					223	334
D-ABC	0.07	10.24	0.1	B	24	36
C-D					26	39
C-A					486	730
C-B					32	48
CD-AB	0.09	7.27	0.1	A	41	61
CD-A					499	749

### Main Results for each time segment

#### 16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	82	21	453	0.181	81	0.0	0.2	10.626	B
A-B	24	6			24				
A-C	173	43			173				
A-D	21	5			21				
AB-CD	50	12	521	0.096	50	0.0	0.1	8.397	A
AB-C	184	46			184				
D-ABC	20	5	464	0.042	19	0.0	0.0	8.900	A
C-D	21	5			21				
C-A	399	100			399				
C-B	26	7			26				
CD-AB	32	8	584	0.056	32	0.0	0.1	7.168	A
CD-A	411	103			411				

#### 17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	98	24	433	0.226	98	0.2	0.3	11.793	B
A-B	29	7			29				
A-C	207	52			207				
A-D	25	6			25				
AB-CD	61	15	511	0.120	61	0.1	0.2	8.805	A
AB-C	219	55			219				
D-ABC	23	6	444	0.053	23	0.0	0.1	9.416	A
C-D	25	6			25				
C-A	476	119			476				
C-B	31	8			31				
CD-AB	40	10	587	0.068	40	0.1	0.1	7.232	A
CD-A	490	122			490				

**17:15 - 17:30**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	120	30	405	0.296	119	0.3	0.5	13.818	B
A-B	35	9			35				
A-C	253	63			253				
A-D	31	8			31				
AB-CD	78	20	501	0.156	78	0.2	0.2	9.361	A
AB-C	265	66			265				
D-ABC	29	7	415	0.069	29	0.1	0.1	10.231	B
C-D	31	8			31				
C-A	584	146			584				
C-B	39	10			39				
CD-AB	51	13	595	0.085	50	0.1	0.1	7.272	A
CD-A	598	149			598				

**17:30 - 17:45**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	120	30	405	0.296	120	0.5	0.5	13.875	B
A-B	35	9			35				
A-C	253	63			253				
A-D	31	8			31				
AB-CD	78	20	501	0.156	78	0.2	0.2	9.373	A
AB-C	265	66			265				
D-ABC	29	7	415	0.069	29	0.1	0.1	10.236	B
C-D	31	8			31				
C-A	584	146			584				
C-B	39	10			39				
CD-AB	51	13	595	0.085	51	0.1	0.1	7.273	A
CD-A	598	149			598				

**17:45 - 18:00**

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	98	24	433	0.226	99	0.5	0.3	11.853	B
A-B	29	7			29				
A-C	207	52			207				
A-D	25	6			25				
AB-CD	62	15	511	0.121	62	0.2	0.2	8.825	A
AB-C	219	55			219				
D-ABC	23	6	444	0.053	23	0.1	0.1	9.424	A
C-D	25	6			25				
C-A	476	119			476				
C-B	31	8			31				
CD-AB	40	10	587	0.068	40	0.1	0.1	7.238	A
CD-A	490	122			490				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-ACD	82	21	453	0.181	82	0.3	0.2	10.703	B
A-B	24	6			24				
A-C	173	43			173				
A-D	21	5			21				
AB-CD	50	13	521	0.097	51	0.2	0.1	8.423	A
AB-C	185	46			185				
D-ABC	20	5	464	0.042	20	0.1	0.0	8.910	A
C-D	21	5			21				
C-A	399	100			399				
C-B	26	7			26				
CD-AB	33	8	584	0.056	33	0.1	0.1	7.176	A
CD-A	411	103			411				



**Appendix 10**  
**Stage One Safety Audit**

**KELVEDON ROAD  
TIPTREE  
ESSEX**

**PROPOSED 3-ARM MINI-  
ROUNDBOUT FOR A  
RESIDENTIAL  
DEVELOPMENT**

**STAGE 1 ROAD SAFETY  
AUDIT**

**November 2019**

**Client: JourneyTransport  
Planning**

# **KELVEDON ROAD TIPTREE ESSEX**

## **PROPOSED 3-ARM MINI ROUNDABOUT FOR A RESIDENTIAL DEVELOPMENT**

### **Stage 1 Road Safety Audit**


**November 2019**

#### **Notice**

This report was produced by *JB Road Safety Consultancy Limited* for *Journey Transport Planning*, for the specific purpose of documenting the Stage 1 Road Safety Audit process undertaken in accordance with GG119.

This report may not be used by any person other than *Journey Transport Planning* without their express permission. In any event, *JB Road Safety Consultancy Limited* accepts no liability for any costs, liabilities or losses arising as a result of the use of or reliance upon the contents of this report by any person other than *Journey Transport Planning*.



Revision Status: Final	Prepared By:	Checked By:	Approved By:	Date Approved:
Audit Team	John Bowman	Beth Newiss		02.11.19
Designers Response	Steve Amann			
Authorities Response				
Audit Response				

# Contents

Section	Page
1. Introduction	3
2. Items Raised During This Stage 1 Road Safety Audit	6
3. Road Safety Audit Team Statement	9

**Appendix A – Drawings and documents supplied by Journey Transport Planning for This Stage 1 Road Safety Audit**

**Appendix B – Annotated Drawing showing the locations of the problems highlighted in This Stage 1 Road Safety Audit**

## DISTRIBUTION RECORD

Issued to	Document Number	Issue Number
<b>FINAL</b>		
Master/File Copy – Author	1	2
Steve Amann Journey Transport Planning	2	2
Steve Amann Journey Transport Planning	3	2

## 1.0 Introduction

- 1.1 This report results from a Stage 1 Road Safety Audit (RSA) carried out on the proposed 3-arm mini roundabout for a residential development of up to 150 dwellings on Kelvedon road in Tiptree, Essex.
- 1.2 The proposals include:
- The provision of a 3-arm mini roundabout on Kelvedon Road;
  - The provision of a 5.5m wide carriageway on the southern arm of the mini roundabout into the development;
  - The provision of indented dropped kerbs and tactile paving on the new southern access road;
  - The provision of 2.0m wide footway, either side of the new access road into the development, and
  - Associated road markings and signage.
- 1.3 The Stage 1 RSA was carried out at the request of Steve Amann, on behalf of the Design Organisation Journey Transport Planning, based at Unit BIC 112, The MedBIC, Alan Cherry Drive, Chelmsford in Essex.
- 1.4 The Audit Brief and Audit Team were approved by Steve Amann, on behalf of the Design Organisation Journey Transport Planning, on the 10<sup>th</sup> October 2019.
- 1.5 The Road Safety Audit Brief was supplied by Steve Amann, (e-mail: steve amann <steve.amann@journeytp.co.uk>, of Journey Transport Planning.
- 1.6 The Audit was carried out on Tuesday 22<sup>nd</sup> October 2019, between 09.50hrs and 10:40hrs. The Audit Team, which is independent of the project design team, has had no involvement with the project.

The Audit Team membership was as follows:

John Bowman            MCIHT MSoRSA  
                                    JB Road Safety Consultancy Ltd

Beth Newiss            MCIHT MSoRSA  
                                    Road Safety Consultant

- 1.7 The report has been prepared in accordance with General Principles and Scheme Governance General Information, GG 119, Road Safety Audit, of the Design Manual for Roads and Bridges. (Formerly HD19/15 Road Safety Audits).
- 1.8 The Audit consisted of a study of the drawings and documents provided by the Design Organisation, and given in *Appendix A* to this report.

- 1.9 No details of any Departures of Standard have been provided to the Audit Team by the Design Organisation.
- 1.10 The site visit was carried out by the Audit Team, together, when the weather was dry and sunny but the road surface was damp. Traffic conditions on Kelvedon Road were constant, including HGV's and LGV's, buses and cars. No pedestrians or pedal cyclists were seen.
- 1.11 Collision data, obtained from Essex County Council by the Design Team has been provided to the Audit Team covering Kelvedon Road in the vicinity of the proposed scheme. This shows that there have been no recorded personal injury collisions in the vicinity of the scheme.
- 1.12 The recommendations in this report are aimed at addressing the road safety problems; however, there may be other alternative acceptable ways to overcome a specific problem, when other practical issues are considered. The recommendations contained herein do not absolve the Designer of his/her responsibilities.
- 1.13 The Overseeing Organisation response to the RSA should be formally recorded and reported to the Designer and the RSA Team so that a record of the Audit process is contained in the *As Built* design pack to be provided and retained by the Overseeing Organisation on final completion.
- 1.14 All problems identified in this Road Safety Audit Report are indicated on a location plan in *Appendix B* to this report.
- 1.15 The Audit Brief supplied by the Design Organisation dated 10<sup>th</sup> October 2019 to the Audit Team outlined the requirements of the scheme to be audited.

## 2 Items Raised During This Stage 1 Road Safety Audit

### 2.1 Local Alignment

#### 2.1.1 PROBLEM

**Locations: A and B** – The eastbound and westbound approaches to the proposed roundabout (Drawing: DR2 Rev 0).

**Summary:** Reduced vehicle pedestrian inter-visibility at the proposed roundabout, could increase the potential risk of rear end shunt collisions occurring.

The scheme drawing indicates that the vehicle / pedestrian inter-visibility splay of 43.0m is to be maintained on the approaches to the roundabout. The proposed stopping sight distances for both eastbound and westbound approaches to the roundabout cross land adjacent to the carriageway.

Concern arises that any existing or proposed vegetation impacting upon the forward visibility on approach to the roundabout could lead to a potential increased risk of rear end shunt collisions occurring, whereby vehicle occupants could sustain personal injury.

#### RECOMMENDATION

It is recommended that at the detailed design stage of the project, details relating to planting and vegetation removal should be provided.

### 2.2 General

#### 2.2.1 PROBLEM

**Locations: C and D** – The eastbound and westbound approaches to the proposed roundabout (Drawing: DR2 Rev 0).

**Summary:** Existing carriageway PSV may not be sufficient to reduce the potential for skidding and enhancing braking capacity on the eastbound and westbound approaches to the proposed roundabout junction resulting in side impact or rear end shunt type collisions.

The scheme proposals indicate that a new roundabout will be constructed on Kelvedon Road approximately 100m to the west of the junction of Kelvedon Road and Oak Road. In operational terms, the introduction of the new roundabout junction and respective give way lines will result in the creation of new braking areas on the eastbound and westbound approaches to the new feature that does not currently exist.

As a result, concern arises that a high skid resistant surface course material may be required on both the eastbound and westbound approaches to the new roundabout junction.

Whilst motorists should always be anticipating the unexpected, sudden or late braking may be required by motorists, particularly those who may be unfamiliar with the area, which could result in potential give way line overshoots and consequent side impact collisions occurring within the circulatory area of the roundabout junction

or rear end shunt collisions occurring between a leading and any following vehicles on the immediate approaches to the give way lines.

### **RECOMMENDATION**

It is recommended that at the detailed design stage of the project, a high skid resistant surface course material should be provided on the northbound and southbound approaches to the proposed junction. The length of skid resistant surface course should be based on the actual 85<sup>th</sup> percentile vehicular approach speeds.

## **2.3 Junctions**

No Problems identified in this category at the Stage 1 Road Safety Audit.

## **2.4 Walking, Cycling and Horse Riding**

No Problems identified in this category at the Stage 1 Road Safety Audit.

## **2.5 Traffic Signs, Carriageway Markings and Lighting**

### **2.5.1 PROBLEM**

**Location:** The approaches to the proposed roundabout (Drawing: DR2 Rev 0)

**Summary:** Give Way road markings are proposed on each approach to the mini roundabout. However, no road signs supporting the road markings have been shown. Lack of supporting information could result in late braking resulting in side impact or rear end shunt type collisions.

The scheme proposals indicate that a new roundabout will be constructed on Kelvedon Road approximately 100m to the west of the junction of Kelvedon Road and Oak Road. In operational terms, the introduction of the new roundabout junction and respective give way lines will result in the creation of new braking areas on the eastbound and westbound approaches to the new feature that does not currently exist.

However, no Give Way road signs, specifically on the westbound approach supporting the road markings have been provided. As a result, concern arises that road users wishing to exit from the new development may find that by giving way to traffic from the right, as is the principal for mini-roundabouts, they are faced with a continual flow of road users at peak hours, increasing the risk of them entering the roundabout in the face of oncoming road users increasing the risk of side impact or rear end shunt type collisions on the circulatory area of the roundabout.

### **RECOMMENDATION**

It is recommended that at the detailed design stage of the project, Give Way road signs should be provided on the western approach to the roundabout on Kelvedon Road.

### 3 Road Safety Audit Team Statement

We certify that this audit has been undertaken in accordance with the principles of DMRB GG 119.

AUDIT TEAM LEADER:

**Name: John Bowman MCIHT MSoRSA**

Position: Director

Organisation: JB Road Safety Consultancy Ltd

Address: 12 Dorset Avenue, Gt Baddow, Chelmsford, Essex, CM2 9TZ

Signed



Date 4<sup>th</sup> November 2019

AUDIT TEAM MEMBER:


**Name: Beth Newiss  
MCIHT MSoRSA**

Position: Road Safety Consultant

Organisation: JB Road Safety Consultancy Ltd

Address: 12 Dorset Avenue, Gt Baddow, Chelmsford, Essex, CM2 9TZ

Signed



Date 4<sup>th</sup> November 2019

Audit Team Leader's Contact Details:

Direct Telephone: 07775 631650

Kelvedon Road, Tiptree, Essex.  
Proposed 3-Arm Mini Roundabout for a Residential Development  
Stage 1 Road Safety Audit – Final

Email address: [javbowman@btinternet.com](mailto:javbowman@btinternet.com)



# Appendix A

(Details of the Drawings and Documents Supplied by the Client for  
This Stage 1 Road Safety Audit)

Drawing Number DR2 Rev 0 Kelvedon Road, Tiptree – Proposed Mini-roundabout Access

Drawing Number DR3 Rev 0 Kelvedon Road, Tiptree – Articulated HGV Swept Path 1 of 3

Drawing Number DR3 Rev 0 Kelvedon road, Tiptree – Articulated HGV Swept Path 2 of 3

Drawing Number DR4 Rev 0 Kelvedon road, Tiptree – Articulated HGV Swept Path 3 of 3


#### Other Documents

Road Safety Audit Brief – Journey Transport Planning

Transport Assessment – Journey Transport Planning – January 2019

# **Appendix B**

(Annotated Drawing Showing Locations of Problems  
Identified in This Stage 1 Road Safety Audit)



client: Marden Homes	date: 01/10/2018	scale: 1:500
project: Kelvedon Road Tiptree	status: Planning (not for construction)	revision:
discipline: Transport Planning	project no: JTP 07718	sheet no: SAA
		sheet no: DR2



**Audit Team Leader's Contact Details:**

JB Road Safety Consultancy Ltd

12 Dorset Avenue

Chelmsford

Essex CM2 9TZ

Telephone: (M) 07775 631650 (H) 01245 264419

Email address: [javbowman@btinternet.com](mailto:javbowman@btinternet.com)